


VENEER LINTELS



MARK	SIZE	MAX. SPAN (UNO)
VL4	L4 x 4 x 5/16	6'-0"
VL6	L6 x 4 x 5/16 LLV	8'-4"
VL8	L8 x 4 x 7/16 LLV	10'-8"


VL(d)

VENEER LINTEL NOTES

1. LINTELS SHALL BEAR ON SOLID MASONRY OR ON TWO CMU COURSES FULLY GROUTED.
2. FURNISH AND INSTALL ALL LOOSE LINTELS REQUIRED FOR ALL OPENINGS IN MASONRY, INCLUDING MECHANICAL AND ELECTRICAL WORK, WHETHER SPECIFICALLY NOTED ON DRAWINGS OR NOT.
3. ALL LINTELS AT EXTERIOR LOCATIONS OR OTHERWISE SUBJECT TO WEATHER OR CORROSIVE ATMOSPHERE SHALL BE GALVANIZED.
4. PROVIDE 6" MINIMUM BEARING EACH END.
5. PROVIDE TWO LAYERS OF 15-MIL PLASTIC VAPOR BARRIER BELOW ALL LINTEL BEARINGS AND CAULK FACE JOINT.

*NOTE FOR "VL8" LINTELS: SPECIAL VENEER SHAPES MUST BE USED, OR TYPICAL SHAPES MUST BE MODIFIED, TO ACCOMMODATE ANGLE THICKNESS AND MAINTAIN EVEN MORTAR JOINT THICKNESS AT BEARING

ANGLE LINTELS




AL(d)

MECHANICAL STEEL ANGLE LINTEL NOTES

1. LINTELS ARE FOR CONCEALED (ABOVE-CEILING) MECHANICAL PENETRATIONS.
2. LINTELS SHALL BEAR A MINIMUM OF 6" EACH END ON SOLID OR GROUT-FILLED MASONRY.
3. PROVIDE TWO LAYERS OF 15-MIL PLASTIC VAPOR BARRIER BELOW ALL LINTEL BEARINGS AND CAULK FACE JOINT.

MARK	SIZE (8" CMU)	SIZE (12" CMU)	MAX. SPAN (UNO)
AL4	(2) L4 x 4 x 5/16	(2) L6 x 4 x 5/16 LLH	6'-0"
AL6	(2) L6 x 4 x 5/16 LLV	(2) L6 x 6 x 5/16	8'-4"
AL8	(2) L8 x 4 x 7/16 LLV	(2) L8 x 6 x 7/16 LLV	10'-8"



AT CORNERS


AT ENDS

- NOTE:
- 1) VERT. BARS TO MATCH SIZE OF WALL REINF. NOTED ON PLAN.
 - 2) IF SIZE OF REINF. IN INTERSECTING WALLS VARIES, PROVIDE LARGER BARS AT LOCATIONS SHOWN.

NOTE: ALTERNATE BLOCK COURSES, TYP.

AT INTERSECTION


TYPICAL REINFORCING AT LOAD-BEARING CMU WALLS



TYP. NON-LOAD-BEARING CMU PERPENDICULAR TO WOOD FRAMING

SECTION


1



TYP. NON-LOAD-BEARING CMU PARALLEL TO WOOD FRAMING

SECTION

2




SECTION

6


SECTION

3



SECTION

4




TYPICAL TOP PLATE SPLICE

SECTION

5

TYPICAL NOTE:
EACH END OF LATERAL BRIDGING MUST BE RIGIDLY FIXED OR OTHERWISE PREVENTED FROM HORIZONTAL MOVEMENT



BRIDGING CONNECTION

SECTION

9

SECTION

10

SECTION

6

SECTION


7

SECTION

8

SHEAR WALL CONSTRUCTION SCHEDULE			
MARK	WALL CONSTRUCTION		
	END STUDS	SIMPSON HOLD-DOWN	STRAPPING
SW1	(3) 14 GA. (68 MIL) MATCH DEPTH OF ADJACENT WALL STUDS	-	FS600-54 ONE FACE
SW2	(3) 14 GA. (68 MIL) MATCH DEPTH OF ADJACENT WALL STUDS	S/HDU-6	FS600-54 ONE FACE
SW3	(3) 14 GA. (68 MIL) MATCH DEPTH OF ADJACENT WALL STUDS	S/HDU-4	FS600-54 EACH FACE
SW4	(3) 14 GA. (68 MIL) MATCH DEPTH OF ADJACENT WALL STUDS	S/HDU-6	FS600-54 EACH FACE

NOTES: 1. WHERE STUD MUST BE CUT DUE TO THE PLACEMENT OF ANCHORS BOLTS OR OTHER PRODUCTS, AN ADDITIONAL STUD SHALL BE INSERTED ALONG SIDE.



4/3/2020 3:47:41 PM

App Architecture

creative focused design

615 Woodside Drive, Englewood, Ohio 45322
T 937.836.8898 F 937.832.3696
www.app-arch.com



Beavercreek Township

Fire Station No. 65


1777 Trebein Road, Beavercreek Township, Ohio 45385


ISSUE:		
NO.	DATE	DESCRIPTION
	04/03/2020	FOR CONSTRUCTION

DATE	04/03/2020
JOB NO.	3541.00
DRAWN	MJI
CHECKED	SRM
CAD	CAD

COPYRIGHT © 2020 App Architecture, Inc.
TITLE
TYPICAL DETAILS

SHEET NO.
S2.03






Beavercreek Township
Fire Station No. 65
1777 Trebein Road, Beavercreek Township, Ohio 45385


ISSUE:		
NO.	DATE	DESCRIPTION
	04/03/2020	FOR CONSTRUCTION

DATE	04/03/2020
JOB NO.	3541.00
DRAWN	MJI
CHECKED	SRM
CAD	CAD

COPYRIGHT © 2020 App Architecture, Inc.
TITLE
FRAMING ELEVATIONS

SHEET NO.
S2.05






ISSUE:		
NO.	DATE	DESCRIPTION
	04/03/2020	FOR CONSTRUCTION

DATE	04/03/2020
JOB NO.	3541.00
DRAWN	MJI
CHECKED	SRM
CAD	CAD


TITLE
FOUNDATION DETAILS

SHEET NO.
S3.02



ISSUE:		
NO.	DATE	DESCRIPTION
	04/03/2020	FOR CONSTRUCTION

DATE	04/03/2020
JOB NO.	3541.00
DRAWN	MJI
CHECKED	SRM
CAD	CAD




Beavercreek Township
Fire Station No. 65
1777 Trebein Road, Beavercreek Township, Ohio 45385


ISSUE:		
NO.	DATE	DESCRIPTION
	04/03/2020	FOR CONSTRUCTION


DATE	04/03/2020
JOB NO.	3541.00
DRAWN	MJI
CHECKED	SRM
CAD	CAD

COPYRIGHT © 2020 App Architecture, Inc.
TITLE
FOUNDATION DETAILS

SHEET NO.
S3.04








Beavercreek Township
Fire Station No. 65
1777 Trebein Road, Beavercreek Township, Ohio 45385

ISSUE:		
NO.	DATE	DESCRIPTION
	04/03/2020	FOR CONSTRUCTION

DATE	04/03/2020
JOB NO.	3541.00
DRAWN	MJI
CHECKED	SRM
CAD	CAD


TITLE
FRAMING DETAILS

SHEET NO.
S3.14



STORM SHELTER FOUNDATION PLAN

1/4" = 1'-0"




STORM SHELTER FRAMING PLAN

1/4" = 1'-0"


- STORM SHELTER ROOF FRAMING NOTES
- DESIGN LIVE/SNOW LOADS:
 - ROOF LIVE: 268 PSF
 - WIND UPLIFT: -209 PSF (INTERIOR ZONES), -292 PSF (WITHIN 3'-FT. OF EDGES), -388 PSF (WITHIN 6'-FT. OF CORNERS)
 - ROOF CONSTRUCTION:
 - 8" (OVERALL) CONCRETE SLAB W/ #5 REINFORCING BARS AT 12 INCHES ON CENTER EACH WAY, TOP AND BOTTOM.
 - PROVIDE PLATE SHROUDS PER SECTION 3/S4.02 AT ALL WALL OPENINGS (MECHANICAL, ELECTRICAL, PLUMBING, ETC.) EXCEEDING 3-1/2 SQUARE INCHES OR 2-1/16 INCH DIAMETER.
 - CONSTRUCT CORNERS OF STORM SHELTER MASONRY WALLS PER DETAIL 4/S4.02.
 - SEE SHEET S0.01 FOR GENERAL STRUCTURAL INFORMATION.

- GENERAL STORM SHELTER NOTES
- DESIGN CRITERIA:
 - TYPE OF STORM SHELTER: COMMUNITY TORNADO
 - MINIMUM SOIL BEARING PRESSURE: 3000 PSF
 - ROOF LIVE LOADS:
 - SHELTER ROOF: 100 PSF
 - WIND LOADS:
 - BASIC WIND SPEED (V_u): 250 MPH
 - EXPOSURE CATEGORY: EXPOSURE C
 - INTERNAL PRESSURE COEFF. (G_{cp1}): +/- 0.55
 - TOPOGRAPHIC FACTOR (K_{zt}): 1.0
 - DIRECTIONALITY FACTOR (K_d): 1.0
 - THE STORM SHELTER AREA HAS BEEN DESIGNED IN ACCORDANCE WITH THE STRUCTURAL PROVISIONS OF ICC 500-2014, "STANDARD FOR THE DESIGN AND CONSTRUCTION OF STORM SHELTERS".
 - IMPACT RESISTANCE:
 - A. WALL AND ROOF SYSTEMS HAVE BEEN SELECTED FOR DEBRIS IMPACT RESISTANCE TESTED IN ACCORDANCE WITH ASTM E 1886. SEE THE "SUMMARY ON DEBRIS IMPACT TESTING OF BUILDING ASSEMBLIES" BY TEXAS TECH UNIVERSITY (et. al.), DATED AUGUST 2006 FOR REFERENCED TEST SPECIMEN NUMBERS.
 - B. WALL SYSTEMS ARE TO BE 8 INCH MINIMUM REINFORCED CONCRETE MASONRY WITH #4 VERTICAL REINFORCING BARS GROUTED INTO EVERY CELL. ASSEMBLY HAS BEEN TESTED FOR A 15-POUND 2x4 TRAVELING AT 100 MPH PER TTU TABLE A.5, TEST NO. 1.
 - C. ROOF SYSTEMS ARE TO BE 4-INCH MINIMUM REINFORCED CONCRETE WITH #4 REINFORCING BARS AT 12 INCHES O.C. EACH WAY. ASSEMBLY HAS BEEN TESTED FOR A 15-POUND 2x4 TRAVELING AT 67 MPH PER TTU TABLE A.6, TEST NO. 37.
 - OPENINGS AND WALL JOINTS:
 - A. WINDOW AND DOOR SYSTEMS ARE TO BE SELECTED TO WITHSTAND THE DESIGN WIND LOADS SPECIFIED BELOW, AND FOR DEBRIS IMPACT RESISTANCE TESTED IN ACCORDANCE WITH ASTM E 1886 FOR A 15-POUND 2x4 TRAVELING AT 100 MPH.
 - B. PROVIDE PLATE SHROUDS AS INDICATED AT ALL OPENINGS (MECHANICAL, ELECTRICAL, PLUMBING, ETC.) IN THE STORM SHELTER ENVELOPE EXCEEDING 1 7/8 INCH SQUARE OR 1 5/8 INCH DIAMETER.
 - C. ALL VERTICAL CONTROL JOINTS IN MASONRY CONSTRUCTION ARE TO BE SEALED IN ACCORDANCE WITH TMS 602, SECTION 2.5 A; JOINT WIDTH MAY NOT EXCEED 3/8".



SECTION 1

3/4" = 1'-0"



SECTION 2

3/4" = 1'-0"

- STORM SHELTER QUALITY ASSURANCE PLAN
- JGA PROJECT NAME: BEAVERCREEK TOWNSHIP FIRE STATION NO. 65
JGA PROJECT NUMBER: 17.05.097
- PRIOR TO CONSTRUCTION OF THE STORM SHELTER PORTION OF THE PROJECT, THE OWNER IS TO RETAIN AN INDEPENDENT AGENCY TO PERFORM THE SPECIAL INSPECTIONS, TESTING, AND STRUCTURAL OBSERVATIONS REQUIRED IN THIS QUALITY ASSURANCE PLAN. WHERE APPLICABLE, INDIVIDUALS PERFORMING SPECIAL INSPECTIONS AND TESTING ARE TO BE QUALIFIED THROUGH RECOGNIZED INDUSTRY CERTIFICATION. INDIVIDUALS PERFORMING STRUCTURAL OBSERVATIONS ARE TO BE REGISTERED DESIGN PROFESSIONALS IN THE JURISDICTION OF THE PROJECT.
 - THE REQUIREMENTS SPECIFIED IN THIS QUALITY ASSURANCE PLAN ARE APPLICABLE TO THE STORM SHELTER PORTION OF THE PROJECT. ITS REFERENCED DETAILS, AND ALL COMPONENTS THEREOF. SEE THE PLANS FOR AREA(S) DESIGNATED AS PART OF THE STORM SHELTER CONSTRUCTION.
 - ON A REGULAR BASIS, THE SPECIAL INSPECTION AND STRUCTURAL OBSERVATION AGENCY SHALL SUBMIT WRITTEN REPORTS IDENTIFYING DEFICIENCIES IN THE STORM SHELTER CONSTRUCTION. AT THE COMPLETION OF THE STORM SHELTER CONSTRUCTION, THE AGENCY SHALL SUBMIT A STATEMENT INDICATING THAT ALL DEFICIENCIES IDENTIFIED DURING CONSTRUCTION HAVE BEEN PROPERLY ADDRESSED, AND THAT STRUCTURAL OBSERVATIONS HAVE BEEN REGULARLY PERFORMED. ALL REPORTS ARE TO BE SUBMITTED TO THE OWNER, ARCHITECT, CONSTRUCTION MANAGER, AND THE AUTHORITY HAVING JURISDICTION.
 - EACH CONTRACTOR RESPONSIBLE FOR CONSTRUCTING ELEMENTS OF THE STORM SHELTER SHALL SUBMIT A WRITTEN STATEMENT OF RESPONSIBILITY TO THE OWNER, ARCHITECT, CONSTRUCTION MANAGER, AND THE AUTHORITY HAVING JURISDICTION. PARTIES RESPONSIBLE FOR THIS STATEMENT INCLUDE, BUT ARE NOT LIMITED TO, THE SITE GRADING CONTRACTOR, CAST-IN-PLACE CONCRETE SUPPLIER AND CONTRACTOR, STRUCTURAL STEEL FABRICATOR AND ERECTOR, MASONRY CONTRACTOR, REINFORCING STEEL FABRICATOR AND IRON WORKERS, PRECAST MANUFACTURER AND ERECTOR, DOOR MANUFACTURER AND INSTALLER, AND OPENING PROTECTIVE DEVICE FABRICATOR AND ERECTOR. THIS STATEMENT IS TO INCLUDE THE FOLLOWING:
 - ACKNOWLEDGMENT OF AWARENESS OF THE SPECIAL REQUIREMENTS IN THE QUALITY ASSURANCE PLAN.
 - ACKNOWLEDGMENT THAT CONTROL WILL BE EXERCISED TO OBTAIN COMPLIANCE WITH THE CONSTRUCTION DOCUMENTS.
 - PROCEDURES FOR EXERCISING CONTROL WITHIN THE CONTRACTOR'S ORGANIZATION, THE METHOD AND FREQUENCY OF REPORTING, AND THE DISTRIBUTION OF REPORTS.
 - IDENTIFICATION AND QUALIFICATIONS OF THE PERSON(S) EXERCISING SUCH CONTROL AND THEIR POSITION(S) IN THE ORGANIZATION.
 - THE FOLLOWING SPECIAL INSPECTIONS AND TESTING OF THE STORM SHELTER CONSTRUCTION ARE TO BE PERFORMED AS PART OF THIS QUALITY ASSURANCE PLAN. THESE REQUIREMENTS ARE IN ADDITION TO THE TESTING AND INSPECTIONS REQUIRED FOR THE REMAINDER OF THE BUILDING:
 - SOILS
 - PERIODICALLY INSPECT SOILS BELOW FOOTINGS FOR ADEQUATE BEARING CAPACITY AND CONSISTENCY WITH GEOTECHNICAL REPORT. INSPECT REMOVAL OF UNSUITABLE MATERIAL AND PREPARATION OF SUBGRADE PRIOR TO PLACEMENT OF CONTROLLED FILL.
 - PERIODICALLY VERIFY DEPTH AND WIDTH OF FOUNDATION EXCAVATIONS.
 - CONCRETE (FOOTINGS, PIERS, TOPPING SLABS, SLABS ON METAL DECK, SLABS ON GRADE, CAPS/ROOFS)
 - PERIODICALLY INSPECT SIZE, SPACING, COVER, POSITIONING, AND GRADE OF REINFORCING STEEL. VERIFY THAT REINFORCING BARS ARE FREE OF FORM OIL OR OTHER DELETERIOUS MATERIALS. INSPECT BAR LAPS AND MECHANICAL SPLICES. VERIFY THAT BARS ARE ADEQUATELY TIED AND SUPPORTED ON CHAIRS OR BOLSTERS.
 - PERIODICALLY INSPECT SIZE, POSITIONING, AND EMBEDMENT OF ANCHOR RODS, WELD PLATES, AND ALL OTHER CAST-IN EMBEDDED ITEMS. INSPECT CONCRETE PLACEMENT AND CONSOLIDATION AROUND ANCHORS.
 - CONTINUOUSLY INSPECT SIZE, POSITIONING, EMBEDMENT, AND INSTALLATION OF POST-INSTALLED CHEMICAL AND MECHANICAL ANCHORS. VERIFY INSTALLATION PROCEDURE IS IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS. PULL-TEST ANCHORS THAT ARE DEEMED SUSPECT DUE TO IMPROPER TORQUE AND/OR INADEQUATE EMBEDMENT DEPTH.
 - PERIODICALLY VERIFY USE OF PROPER MIX DESIGN.
 - PERIODICALLY VERIFY FORM WORK FOR SHAPE, LOCATION, AND DIMENSIONS OF CONCRETE BEING FORMED.
 - PERIODICALLY INSPECT PLACEMENT OF CONCRETE. VERIFY THAT CONCRETE CONVEYANCE AND DEPOSITING AVOIDS SEGREGATION OR CONTAMINATION. VERIFY THAT CONCRETE IS PROPERLY CONSOLIDATED. INSPECT CURING, COLD-WEATHER PROTECTION, AND HOT-WEATHER PROTECTION PROCEDURES.
 - PERIODICALLY SAMPLE AND TEST CONCRETE FOR COMPRESSIVE STRENGTH, SLUMP, AIR CONTENT, AND TEMPERATURE. SAMPLE EACH 50 CUBIC YARDS OF CONCRETE, OR FRACTION THEREOF, PLACED IN ANY ONE DAY.
 - MASONRY
 - PERIODICALLY INSPECT PROPORTIONING, MIXING, AND RETEMPERING OF MORTAR AND GROUT. INSPECT CONSTRUCTION OF MORTAR JOINTS INCLUDING TOOLING AND FILLING OF HEAD JOINTS.
 - PERIODICALLY INSPECT SIZE, LAYOUT, BONDING, GROUT SPACE, AND PLACEMENT OF MASONRY UNITS.
 - PERIODICALLY INSPECT PLACEMENT, SIZE, GRADE, POSITIONING, AND LAPPING OF REINFORCING STEEL.
 - CONTINUOUSLY INSPECT PLACEMENT AND CONSOLIDATION OF GROUT. INSPECT MASONRY CLEAN-OUTS FOR HIGH-LIFT GROUTING.
 - PERIODICALLY INSPECT SIZE, POSITIONING, AND EMBEDMENT OF ANCHOR RODS, WELD PLATES, AND ALL OTHER CAST-IN EMBEDDED ITEMS. INSPECT CONCRETE PLACEMENT AND CONSOLIDATION AROUND ANCHORS.
 - CONTINUOUSLY INSPECT SIZE, POSITIONING, EMBEDMENT AND INSTALLATION OF POST-INSTALLED CHEMICAL AND MECHANICAL ANCHORS. VERIFY INSTALLATION PROCEDURE IS IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS. PULL-TEST ANCHORS THAT ARE DEEMED SUSPECT DUE TO IMPROPER TORQUE AND/OR INADEQUATE EMBEDMENT DEPTH.
 - PERIODICALLY INSPECT COLD-WEATHER PROTECTION AND HOT-WEATHER PROTECTION PROCEDURES. VERIFY THAT WALL CAVITIES ARE PROTECTED AGAINST PRECIPITATION.
 - PERIODICALLY SAMPLE AND TEST COMPRESSIVE STRENGTH OF MORTAR AND GROUT CUBE SAMPLES. TEST COMPRESSIVE STRENGTH OF ASSEMBLED MASONRY PRISMS.
 - OPENING PROTECTIVE DEVICES
 - CONTINUOUSLY INSPECT INSTALLATION OF DOOR ANCHORAGES AND ANCHORAGE OF PROTECTIVE BAFFLES FOR OPENINGS.
 - UPON COMPLETION, VERIFY THE PROPER OPERATION OF DOORS AND SHUTTERS. CONFIRM MAXIMUM ALLOWABLE GAPS AT THRESHOLDS, SILLS, JAMBS, AND HEADS OF OPENING LEAFS.
 - THE FOLLOWING STRUCTURAL OBSERVATIONS OF THE STORM SHELTER CONSTRUCTION ARE TO BE PERFORMED AS PART OF THIS QUALITY ASSURANCE PLAN. THESE OBSERVATIONS ARE TO VISUALLY VERIFY THAT THE IDENTIFIED ASSEMBLIES ARE BEING BUILT IN GENERAL CONFORMANCE WITH THE CONSTRUCTION DOCUMENTS. ADDITIONAL OBSERVATIONS OF THE CONSTRUCTION ARE TO BE PERFORMED AT THE OBSERVER'S DISCRETION.
 - FOUNDATIONS
 - VERIFY THAT DOWEL BARS IN FOUNDATIONS AND SLABS ARE BEING PROVIDED WHERE INDICATED. VERIFY THAT DOWELS HAVE BEEN SHORTENED AT LOCATIONS WHERE THE HOST BUILDING IS DESIGNED TO BREAK-FREE FROM THE STORM SHELTER CONSTRUCTION.
 - VERIFY THAT ANCHOR BOLTS HAVE BEEN PROVIDED WITH SUFFICIENT LENGTHS TO RECEIVE FURTHER CONSTRUCTION. VERIFY THAT ANCHORS HAVE NOT BEEN BENT OR OTHERWISE MODIFIED.
 - WALLS
 - VERIFY THAT OPENINGS AND PORTALS ARE BEING BUILT AS INDICATED.
 - VERIFY THAT SUFFICIENT LAP LENGTHS ARE BEING PROVIDED BETWEEN SEQUENCES OF CONSTRUCTION.
 - VERIFY THAT CAST-IN AND POST-INSTALLED ANCHORS HAVE SUFFICIENT LENGTH TO RECEIVE FURTHER CONSTRUCTION. VERIFY THAT ANCHORAGES HAVE NOT BEEN BENT OR OTHERWISE MODIFIED.
 - VERIFY THAT PROPER CAST-IN ITEMS FOR DOORS AND SHUTTERS ARE BEING PROVIDED.
 - VERIFY THAT VERTICAL CONTROL JOINTS ARE 3/8" OR LESS IN WIDTH, AND HAVE BEEN FILLED ACCORDING TO TMS 602 FOR MASONRY OR ASTM C920 FOR CONCRETE.
 - VERIFY THAT BOND PATTERN AT CORNERS HAS BEEN CONSTRUCTED AS INDICATED.
 - ROOFS
 - VERIFY THAT ANCHORAGES BETWEEN THE STORM SHELTER WALLS AND ROOFS ARE BEING PROVIDED AS INDICATED.
 - VERIFY THAT MEMBER BRACING, CONFIGURATION, AND CONNECTIONS HAVE BEEN PROVIDED AS INDICATED.
 - VERIFY THAT DOWELS, BARS, AND/OR ANCHORAGES HAVE BEEN SHORTENED AT LOCATIONS WHERE THE HOST BUILDING IS DESIGNED TO BREAK-FREE FROM THE STORM SHELTER CONSTRUCTION.
 - VERIFY FILLING OF GAPS AND JOINTS BETWEEN ROOF FRAMING MEMBERS, AND AT BEARING LOCATIONS.
 - OPENINGS
 - VERIFY THAT POST-INSTALLED ANCHORAGES OF OPENING PROTECTIVE DEVICES HAVE BEEN INSTALLED.
 - VERIFY THAT PROTECTIVE BAFFLES HAVE BEEN PROVIDED FOR ALL PENETRATIONS THROUGH THE STORM SHELTER ENVELOPE.

App Architecture
creative focused design

615 Woodside Drive, Englewood, Ohio 45322
T 937.836.8898 F 937.832.3696
www.app-arch.com

STATE OF OHIO
PROFESSIONAL ARCHITECT
STEVEN R. McCLAREN
E-513993

Jezerinac Geers
Structural Engineering

Beavercreek Township
Fire Station No. 65
1777 Trebein Road, Beavercreek Township, Ohio 45385


ISSUE:
NO. DATE DESCRIPTION
04/03/2020 FOR CONSTRUCTION

DATE	04/03/2020
JOB NO.	3541.00
DRAWN	MJI
CHECKED	SRM
CAD	CAD

COPYRIGHT © 2020 App Architecture, Inc.

TITLE
STORM SHELTER

SHEET NO.
S4.01



4/3/2020 3:47:49 PM

App Architecture

creative focused design

615 Woodside Drive, Englewood, Ohio 45322
T 937.836.8898 F 937.832.3696
www.app-arch.com



Jezerinac Geers

Structural Engineering

Beavercreek Township

Fire Station No. 65


1777 Trebein Road, Beavercreek Township, Ohio 45385

ISSUE:		
NO.	DATE	DESCRIPTION
	04/03/2020	FOR CONSTRUCTION

DATE	04/03/2020
JOB NO.	3541.00
DRAWN	MJI
CHECKED	SRM
CAD	CAD

COPYRIGHT © 2020 App Architecture, Inc.
TITLE
STORM SHELTER

SHEET NO.
S4.02



- # CONSTRUCTION NOTES**
1. 6" COMBINATION WATER SERVICE BY SITE UTILITY CONTRACTOR.
 2. FIRE SERVICE RISER WITH DOUBLE DETECTOR CHECK BACKFLOW PREVENTOR IN THE VERTICAL POSITION. SEE DETAIL THIS SHEET
 3. 3" DOMESTIC WATER SERVICE BY P.C.. SEE DETAIL SHEET P4.3.
 4. 5" STORTZ CONNECTION.
 5. 2.5" FIRE DEPARTMENT VALVE WITH 1.5" ADAPTER ON EXPOSE PIPE DROP FOR FILLING TANKER TRUCK. SEE SHEET F2.2 FOR CONTINUATION.
 6. 4" SPRINKLER RISER UP. SEE SHEET F2.2 FOR CONTINUATION.
 7. 2.5" FIRE WATER UP AND ACROSS MEZZANINE TO FIRE DEPARTMENT VALVE (NOTE 5). SEE SHEET F2.2 FOR CONTINUATION.
 8. SPRINKLER PIPING FROM MEZZANINE. EXTEND TO FIRST FLOOR SPRINKLER SYSTEM.


STORM SHELTER NOTES

PENETRATIONS THROUGH THE STORM SHELTER ENVELOPE LARGER THAN 3-1/2 SQUARE INCHES IN AREA FOR RECTANGULAR OPENINGS OR 2-1/16" IN DIAMETER SHALL BE CONSIDERED OPENINGS AND SHALL BE PROVIDED WITH AN OPENING PROTECTIVE DEVICE. REFERENCE STRUCTURAL DRAWINGS.

ISSUE:		
NO.	DATE	DESCRIPTION
	04/03/20	FOR CONSTRUCTION

DATE	04/03/20
JOB NO.	3541.00
DRAWN	DEG
CHECKED	DEG
CAD	18102F2.1.dwg



COPYRIGHT © 2020 App Architecture, Inc.	
TITLE	LEVEL 1 FLOOR PLAN
SHEET NO.	F2.1



- # CONSTRUCTION NOTES
1. PIPING FROM FIRE SERVICE RISER BELOW. SEE LEVEL 1 FLOOR PLAN.
 2. PIPING RUN AT UNDERSIDE OF SLOPED STRUCTURE.
 3. DROP PIPING TO NEAR TOP OF MEZZANINE FLOOR AND RUN THRU WALL INTO SPACE ABOVE LEVEL 1 CEILING. SEE LEVEL 1 FLOOR PLAN FOR CONTINUATION.
 4. ADDITIONAL FLOW SWITCH SERVING ONLY YHT SPRINKLER ON THE MEZZANINE.
 5. 2.5" TANKER FILL LINE DOWN. SEE FIRST FLOOR PLAN FOR CONTINUATION.


MEZZANINE AND UPPER APPARATUS BAY PLAN

SCALE: 1/8" = 1'-0"



App Architecture
creative focused design

615 Woodside Drive, Englewood, Ohio 45322
T 937.836.8698 F 937.832.3696
www.app-arch.com



Beavercreek Township
Fire Station No. 65
1777 Trebin Road, Beavercreek Township, Ohio 45385

ISSUE:		
NO.	DATE	DESCRIPTION
	04/03/20	FOR CONSTRUCTION

DATE	04/03/20
JOB NO.	3541.00
DRAWN	DEG
CHECKED	DEG
CAD	18102F2.2.dwg

COPYRIGHT © 2020 App Architecture, Inc.

TITLE
**MEZZANINE AND
UPPER APPARATUS
BAY PLAN**

SHEET NO.

F2.2

NAUMAN & ZELINSKI LLC.
204 S. Ludlow Street Suite 400 Dayton, Ohio 45402
Phone: (937) 223-3821 • Fax: (937) 223-3849

PLUMBING FIXTURE SCHEDULE

ITEM	FIXTURE DESCRIPTION	FIXTURE	SERVICES					MTG. HGT.	TRIM REQUIREMENTS						NOTES
			H.W.	C.W.	R.O.	SAN.	VENT		SUPPLY	STOPS	WASTE	TRAP	CARRIER	ACCESSORIES	
W1	WATER CLOSET/ FLOOR SET/ FLOOR OUTLET/ VIT. CHINA/ FLUSH VALVE/ 1.6 GPF/ ELONGATED/ OPEN FRONT SEAT W LID	AM. STANDARD # 3040.001	—	1"		4"	2"	—	SLOAN # SLOAN 111	UNIT	UNIT	INTEGRAL	—	BEMIS # 1950SS	
W2	WATER CLOSET/ FLOOR SET/ FLOOR OUTLET/ VIT. CHINA/ FLUSH VALVE/ 1.6 GPF/ ELONGATED/ OPEN FRONT SEAT	AM. STANDARD # 3040.001	—	1"		4"	2"	—	SLOAN # SLOAN 111	UNIT	UNIT	INTEGRAL	—	BEMIS # 1955SSCT	
W3	WATER CLOSET/ FLOOR SET/ FLUSH TANK/ RIGHT HEIGHT/ 1000 G M&P RATED/ OPEN SEAT WITH LID/ ACCESSIBLE	AM. STANDARD # 215AB.004	—	0.5"		4"	2"		UNIT	MCGUIRE # LFBV172	UNIT	INTEGRAL	—	BEMIS # 1950SS	
L1	LAVATORY/ INTEGRAL WITH C'TOP/ SOLID SURFACE/ SINGLE LEVER FAUCET/ POP-UP WASTE/ 1.2 GPM	BY OTHERS	0.5"	0.5"		1.25"	1.25"	34" TO RIM	AM. STANDARD # 1480.101	MCGUIRE # LFBV170	UNIT	MCGUIRE # PW2150WC	—	POWERS # LFE480	
L2	LAVATORY/ INTEGRAL WITH C'TOP/ SOLID SURFACE/ SINGLE LEVER FAUCET/ GRID STRAINER/ 0.5 GPM	BY OTHERS	0.5"	0.5"		1.25"	1.25"	—	AM. STANDARD # 1480.100-F05	MCGUIRE # LFBV170	MGUIRE # 155A	MCGUIRE # PW2150WC	—	POWERS # LFE480	
L3	LAVATORY/ WALL HUNG/ VIT CHINA/ SINGLE LEVER FAUCET/ GRID STRAINER/ 0.5 GPM	AM. STANDARD # 0355.012	0.5"	0.5"		1.25"	1.25"	34" TO RIM	AM. STANDARD # 1480.100-F05	MCGUIRE # LFBV170	UNIT	MCGUIRE # PW2150WC	J.R.SMITH # 0710	POWERS # LFE480	
S1	SINK/ ST. ST./ UNDERCOUNTER MOUNTING/ SINGLE BOWL/ SINGLE LEVER FAUCET W SPRAY	ELKAY # EFRU131610	0.5"	0.5"		1.5"	1.25"	—	AM. STANDARD # 4433.001	MCGUIRE # LFBV170	MCGUIRE # 151A	MCGUIRE # 8912F	—		
S2	SINK/ C'TOP/ DOUBLE BOWL/ SINGLE LEVER FAUCET W SPRAY/ DISPOSAL/ RO FAUCET	ELKAY # LR3319	0.5"	0.5"	0.5"	(2) 1.5"	1.25"	—	AM. STANDARD # 4332.350 WATTS # WTMFAG-C	MCGUIRE # LFBV170	MCGUIRE # 151A	MCGUIRE # 8912F & # 111	—	INSINKERATOR # ESSENTIAL XTR	
S3	SINK/ ST. ST./ C'TOP/ DOUBLE BOWL/ SINGLE LEVER FAUCET W SPRAY	ELKAY # LR2219	0.5"	0.5"		(2) 1.5"	1.25"	—	AM. STANDARD # 4433.001	MCGUIRE # LFBV170	MCGUIRE # 151A	MCGUIRE # 8912F	—		
S4	SINK/ ST. ST./ INTEGRAL W C'TOP/ DOUBLE BOWL/ SINGLE LEVER FAUCET W PULL DOWN SPRAY W COIL/ BASKET STRAINER/ EMERG. DRENCH HOSE WITH MIXING VALVE	BY OTHERS	0.5"	0.5"		(2) 1.5"	1.25"	—	AM. STANDARD # 4332.350	MCGUIRE # LFBV170	MCGUIRE # 151A	MCGUIRE # 8912F & # 111	—	GUARDIAN # G5022-TMV	
SH1	SHOWER/ STALL BY OTHERS/ MIXING VALVE WITH FIXED HEAD AND HAND HELD ON SLIDE BAR/ DIVERTER VALVE IN WALL	BY OTHERS	0.5"	0.5"		2"	1.5"	VALVE 42"	POWERS # E710-M-2-N-Y-W						
SH2	DECONTAM SHOWER STALL/ STALL BY OTHERS/ MIXING VALVE WITH FIXED HEAD AND HAND HELD ON SLIDE BAR/ DIVERTER VALVE IN WALL	BY OTHERS	0.5"	0.5"		3"	1.5"	VALVE 42" HEAD 86"	POWERS # E710-M-2-N-Y-W						
M1	MOP SINK/ FLOOR SET/ 24" SQ. 10" DEEP/ MOLDED STONE/DROP FRONT/ ST. SAT. CAP ON DROP/	FLORESTONE # 91	0.5"	0.5"		3"	1.5"	36" C FAUCET	AM. STANDARD # 8354.112	UNIT	UNIT	SAME AS DWV PIPING	---		
M2	MOP SINK FAUCET ONLY	NONE	0.5"	0.5"		—	—	36" C FAUCET	AM. STANDARD # 8354.112	UNIT	—	—	---		
HR1	HOSE REEL/ WALL MOUNTED/ OPEN/ SPRING DRIVEN/ 75' OF 0.75" HOSE/ 250 PSI MAX	REELCRAFT # GCD83075 OLP	—	0.75"		—	—	SUPPLY @ 36" REEL @ 60"	T&S BRASS # B-2301						
WB1	WASHER UTILITY CONNECTION BOX/ 1/4 TURN BALL VALVES WITH WATER HAMMER ARRESTOR	OATEY # 38655	0.5"	0.5"		2"	1.5"	36"	UNIT	BALL VALVES ABOVE CLG.	UNIT	SAME AS DWV			
WB2	ICE MAKER CONNECTION BOX/ 1/4 TURN BALL VALVE/ 6' ST. ST. HOSE	OATEY # 39142	—	—	0.5"	—	—	24"	UNIT	BALL VALVES ABOVE CLG.					
WB3	WASHER UTILITY CONNECTION BOX/ SUPPLY ONLY/ 1/4 TURN BALL VALVES WITH WATER HAMMER ARRESTOR	OATEY # 38655	0.5"	0.5"		—	—	36"	UNIT	BALL VALVES ABOVE CLG.	UNIT	—			

EQUALS
AMERICAN STANDARD CHINA — KOHLER, ZURN
AMERICAN STANDARD FAUCETS — KOHLER, ZURN, CHICAGO FAUCET.
SLOAN — ZURN, DELANEY
BRADLEY — ACORN, WILLOUGHBY
ELKAY — JUST, ADVANCED TABCO,
WOODFORD — ZURN, J.R.SMITH,
LEONARD — SYMMONS, POWERS, ACORN
J.R.SMITH — SEE SPECIFICATIONS
MCGUIRE — WATTS, BRASSCRAFT

NOTES
1. COORDINATE ROUGH-IN WITH CASEWORK SUPPLIER.
2. TRAP SAME MATERIAL AS SANITARY PIPING.
3. INSTALL PER MANUFACTURER'S RECOMMENDATIONS
4. SINK OUTLET TO BE BACK CENTER.
5. PROVIDE COPPER AIR GAP FITTING FOR DISHWASHER WASTE DEARBORN BRASS # DB-CD-3.
COORDINATE LOCATION CAREFULLY WITH CASEWORK INSTALLER.

GENERAL NOTES - PLUMBING

- A. ALL WORK SHALL BE IN ACCORDANCE WITH THE LATEST VERSION OF THE OHIO BUILDING AND PLUMBING CODES, INCLUDING REFERENCED CODES AND STANDARDS.
- B. OBTAIN A PLUMBING PERMIT AND SECURE INSPECTION AND APPROVAL OF THE CODE OFFICIAL.
- C. COORDINATE EACH ROUGH-IN INSTALLATION REQUIREMENTS AND LOCATIONS WITH OTHER TRADES, ACTUAL EQUIPMENT OR CABINETS PROVIDED AND FILED CONDITIONS BEFORE PERFORMING WORK.
- D. REFER TO ARCHITECTURAL CODE PLANS FOR LOCATIONS OF FIRE WALLS AND SMOKE PARTITIONS.
IN SMOKE PARTITIONS FILL SPACE AROUND PENETRATIONS WITH AN APPROVED MATERIAL TO LIMIT THE FREE PASSAGE OF SMOKE.
IN FIRE WALLS SEAL ALL PENETRATIONS WITH AN APPROVED FIRE STOPPING PRODUCT, SEE SPECIFICATIONS.
- E. REFER TO DIAGRAMS, DETAILS, AND SCHEDULES FOR PIPING AND PIPE SIZES NOT SHOWN ON PLAN OR ON DIAGRAMS.
- F. ALL PIPING IS ABOVE THE CEILING (AT THE CEILING IN EXPOSED STRUCTURE AREAS) AND BELOW THE BOTTOM CHORD OF THE TRUSSES UNLESS OTHERWISE INDICATED ON PLAN. VENT AND NATURAL GAS PIPING MAY BE RUN IN ATTIC SPACES.
- G. ALL EQUIPMENT AND MATERIAL REQUIRED FOR COMPLETE AND FUNCTIONAL PLUMBING SYSTEMS ARE INCLUDED IN THE CONTRACT. THE WORK SCOPE IN THE PROJECT MANUAL DEFINES THE FINAL CONTRACTUAL RESPONSIBILITY TO PROVIDE SUPPORTING EQUIPMENT, MATERIALS, FINISHING, UTILITY COST, ETC (EXAMPLES: CONCRETE PADS, PAINTING, TEMPORARY ELECTRIC/GAS COSTS) FOR THE PLUMBING SYSTEMS. THE WORK SCOPE TAKES PRECEDENCE OVER OTHER SPECIFICATION SECTIONS OR DRAWING REQUIREMENTS.

PLUMBING DRAIN AND CLEANOUT SCHEDULE

DRAIN TYPES		CLEANOUT TYPES		OUTLET SIZE	FEATURES						STRAINER						NOTES
FD – FLOOR DRAIN	FS – FLOOR SINK	FCO – FLOOR CLEANOUT	WCO – WALL CLEANOUT		ANCHOR FLANGE	FLASHING CLAMP	UNDERDECK CLAMP	DOUBLE DRAINAGE	SEDMINT BUCKET	TOP/STRAINER SIZE	FLAT	DOME	OPEN TOP NO GRATE	HALF OPEN	ADJUSTABLE		
RD – ROOF DRAIN	SRD – SECONDARY ROOF DRAIN																
SSD – SECONDARY STORM OUTLET																	
ITEM	DRAIN DESCRIPTION		MANUFACTURER														
FD1	FLOOR DRAIN/CAST IRON BODY AND TOP/ MED DUTY/ LOOSE GRATE		J.R.SMITH # 2110	3"	●					8"ø	●						
FD2	FLOOR DRAIN/CAST IRON BODY/ NICKEL-BRONZE TOP/ ADJUSTABLE		J.R.SMITH # 2005-C06-NB	3"	●					6"ø.	●				1.		
FD3	FLOOR DRAIN/CAST IRON BODY/ NO TOP GRATE/ FLAT GRATE IN BOTTOM/ MED DUTY/		J.R.SMITH # 2130-LG-FBS	4"	●					12"ø			●				
FD4	FLOOR DRAIN/CAST IRON BODY/ NICKEL-BRONZE SQUARE TOP/ ADJUSTABLE		J.R.SMITH # 2005-K06-NB	3"	●					6"SQ	●				1.		
FD5	FLOOR DRAIN/CAST IRON BODY/ NICKEL-BRONZE TOP/ FLAT GRATE IN BOTTOM/ MED DUTY/		J.R.SMITH # 2130-S-FBS-NB	3"	●					12"SQ	●			●	3.		
TD1	TRENCH DRAIN/ HDPE W HEAVY DUTY GRAY IRON FRAME/ DUCTILE IRON SLOTTED GRATE/ DIN/EN 1433 LOAD CLASS F/		POLYCAST # DG0700AA W/ DG0675HD GRATE & DA0642BH LOCK	4"						6" W 20" LONG	●						
TD2	TRENCH DRAIN/ HDPE W HEAVY DUTY GRAY IRON FRAME/ DUCTILE IRON SLOTTED GRATE/ DIN/EN 1433 LOAD CLASS F/		POLYCAST # DG0700AA W/ DG0675HD GRATE & DA0642BH LOCK	4"						6" W 40" LONG	●						
FCO	CLEANOUT/ FLOOR SET/ NICKEL BRONZE TOP/ CAST IRON BODY/ MIP THREADED CONN./ ABS PLUG		J.R.SMITH # 4020S SERIES							6"ø	●				2.		
ECO	EXTRA HEAVY DUTY CLEANOUT/ FLOOR SET/ NICKEL BRONZE TOP/ CAST IRON BODY/ MIP THREADED CONN./ ABS PLUG		J.R.SMITH # 4100S SERIES							6"ø	●				2.		
WCO	CLEANOUT/ WALL MOUNTED/ ST.ST. COVER WITH THREADED BOLT AND BRONZE PLUG		J.R.SMITH # 4472T SERIES							7"ø	●				2.		

- NOTES
1. PROVIDE ASSE 1072 TRAP SEAL PROTECTION DEVICE EQUAL TO MIFAB "MI-GARD" OR J.R.SMITH # 2692
2. CLEANOUT TO BE SAME SIZE AS PIPING FOR PIPING UP TO 4", AND 4" FOR LARGER PIPE SIZES.
3. GRATE TO BE MODIFIED ON SITE TO BE OPEN BELOW INDIRECT LINE.

PLUMBING LEGEND

—	SANITARY DRAIN
- - - -	VENT
— — — —	COLD WATER
—HCW—	HARD COLD WATER (CITY WATER NO SOFTENING)
— — — —	HOT WATER
— — — —	HOT WATER RETURN
—G—	NATURAL GAS
—A—	COMPRESSED AIR
C.O.	CLEAN OUT
—X—	SHUT-OFF VALVE, SEE SCHEDULE FOR TYPE
—Z—	CHECK VALVE
—K—	BALANCING VALVE
—R—	VALVE ON RISER
—S—	UNION, SCREWED
Ⓡ	REGULATOR
Ⓟ	PRESSURE GAUGE
Ⓣ	TEMPERATURE GAUGE
—C—	CONNECTION, BOTTOM
—T—	CONNECTION, TOP
→	INDICATES DIRECTION OF FLOW
—C—	CAP
V.R.	VENT RISER
V.T.R.	VENT THRU ROOF
S.S.	SOIL STACK
V.S.	VENT STACK
D.S.	DOWNSPOUT (STORM)

SEISMIC REQUIREMENTS

THIS PROJECT HAS SEISMIC REQUIREMENTS.
REFER TO DRAWING H0.1.

GENERAL LEGEND

EC	ELECTRICAL CONTRACTOR.
FC	FIRE PROTECTION CONTRACTOR.
GC	GENERAL CONTRACTOR.
HC	HVAC CONTRACTOR.
PC	PLUMBING CONTRACTOR.
TC	TEMPERATURE CONTROLS CONTRACTOR.
NIC	NOT IN CONTRACT.
AFF	ABOVE FINISHED FLOOR — TO BOTTOM OF ITEM UNLESS INDICATED OTHERWISE IN DRAWING.
③	NOTE SYMBOL — APPLIES ONLY TO SHEET ON WHICH IS SHOWN.
②	DETAIL NOTE SYMBOL — APPLIES ONLY TO DETAIL ON WHICH IS SHOWN.
H-1	EQUIPMENT REFERENCE SYMBOL.
FD1	"UP TO" SYMBOL — INDICATES ITEM SERVED ON FLOOR ABOVE.
— — — —	1 HOUR FIRE PROTECTION SEE SPECIFICATION FOR PENETRATION DETAILS.
— — — — —	2 HOUR FIRE PROTECTION SEE SPECIFICATION FOR PENETRATION DETAILS.
— — — — — —	3 HOUR FIRE PROTECTION SEE SPECIFICATION FOR PENETRATION DETAILS.
—	NEW ITEM.

INDEX OF DRAWINGS

SHEET	DRAWING TITLE
P0.1	INDEX, LEGEND, AND SCHEDULES
P2.0F	UNDER FLOOR PIPING PLAN
P2.1	LEVEL 1 FLOOR PLAN
P2.2	MEZZANINE AND UPPER APPARATUS BAY PLAN
P3.1	ENLARGED PLANS
P4.1	MATERIAL SCHEDULES
P4.2	DETAILS
P4.3	DETAILS
P5.1	SOIL, WASTE, AND VENT DIAGRAM

NAUMAN & ZELINSKI LLC.
204 S. Ludlow Street Suite 400 Dayton, Ohio 45402
Phone: (937) 223-3821 — Fax: (937) 223-3849

App Architecture
creative focused design



Beavercreek Township

Fire Station No. 65


ISSUE:		
NO.	DATE	DESCRIPTION
	04/03/20	FOR CONSTRUCTION

DATE	04/03/20
JOB NO.	3541.00
DRAWN	DEG
CHECKED	DEG
CAD	18102P0.dwg

TITLE
INDEX, LEGEND, AND
SCHEDULES

SHEET NO.

P0.1



- # CONSTRUCTION NOTES
1. COMBINED WATER SERVICE BY SITE UTILITY CONTRACTOR.
 2. NATURAL GAS SERVICE BY VECTREN.
 3. OIL INTERCEPTOR. SEE DETAIL SHEET P4.2.
 4. SANITARY PIPING CONTINUED BY SITE UTILITY CONTRACTOR.
 5. ANCHOR CLEANOUT IN 12"X 12" X 6" DEEP CONCRETE PAD WITH TOP AT NEW FINISHED GRADE.
 6. DRAIN TROUGH. TROUGH IS TO BE RECESSED INTO EXTRACTOR/WASHER CONCRETE PAD. SEE LEVEL 1 FLOOR PLAN.
 7. GAS SERVICE BY VECTREN.
 8. UP TO NATURAL GAS METER AND REGULATOR SETTING BY VECTREN.
 9. NATURAL GAS PIPING FROM ABOVE. PROVIDE ANODELESS RISER.
 10. NATURAL GAS PIPING UP TO ABOVE PATIO LEVEL. PROVIDE ANODELESS RISER.
 11. SEWAGE LIFT STATION. SEE CIVIL DRAWINGS.
 12. 1.25" NATURAL GAS UP SEE FIRST FLOOR PLAN SHEET P2.1 FOR CONTINUATION AND SHEET P4.3 FOR SCHEMATIC OF ENTIRE NATURAL GAS SERVICE.
 13. 1.5" HUB DRAIN WITH 2" ADAPTER FOR ICE MAKER DRAIN.
 14. 3" BASIN VENT UP.
 15. GAS PIPING UNDER DRIVE TO BE MINIMUM 48" DEEP.

GENERAL NOTE

ALL PIPING INDICATED ON THIS PLAN IS LOCATED BELOW THE FIRST FLOOR SLAB OR BELOW GRADE UNLESS OTHERWISE NOTED.

App Architecture
creative focused design

615 Woodside Drive, Englewood, Ohio 45322
T 937.836.8698 F 937.832.3696
www.app-arch.com

STATE OF OHIO
JEFFREY D. ZELINSKI
63822
REGISTERED PROFESSIONAL ENGINEER

Beavercreek Township

Fire Station No. 65

1777 Trebin Road, Beavercreek Township, Ohio 45385

ISSUE:

NO.	DATE	DESCRIPTION
	04/03/20	FOR CONSTRUCTION

DATE 04/03/20

JOB NO. 3541.00

DRAWN DEG

CHECKED DEG

CAD 18102P2.0F.dwg


COPYRIGHT © 2020 App Architecture, Inc.

TITLE

UNDER FLOOR PIPING PLAN

SHEET NO.

P2.0F



LEVEL 1 FLOOR PLAN

SCALE: 1/8" = 1'-0"



CONSTRUCTION NOTES

1. SEE ENLARGED EMS AND WATER SERVICE ROOMS PLAN SHEET P3.1 FOR PIPING IN THIS AREA.
2. SEE ENLARGED KITCHEN AREA PLAN SHEET P3.1 FOR PIPING IN THIS AREA.
3. SEE ENLARGED BATHROOM AREA PLAN SHEET P3.1 FOR PIPING IN THIS AREA.
4. FREEZE-PROOF HOSE BIBB IN RECESSED BOX. WOODFORD # B65 OR APPROVED EQUAL. MOUNT APPROX. 24" A.F.F.
5. INTERIOR HOSE BIBB. WOODFORD # 46-PC-VB WITH BRASS HANDLE OR APPROVED EQUAL. MOUNT 24" A.F.F.
6. GAS SUPPLY BOX FOR GRILL. MOUNT 18" A.F.F. BURNABY # G0101-SS-50-BI OR APPROVED EQUAL. GAS PIPING TO ENTER BOX FROM BOTTOM AND TURN AND RUN THRU WALL IN SLEEVE.
7. NATURAL GAS SERVICE REGULATOR AND METER BY VECTREN. VALVE AND CONNECT TO OUTLET. SEE DETAIL SHEET P4.3.
8. DROP GAS PIPING INTO GROUND EXTEND PIPING TO EMERGENCY GENERATOR. PROVIDE ANODELESS RISER. SEE DETAIL SHEET P4.3.
9. DROP 1" GAS IN WALL TO THE GRILL.
10. PIPING CONTINUED ON UPPER APPARATUS BAY PLAN. SEE SHEET P2.2.
11. 3" BASIN VENT FROM BELOW.
12. 2" HOT WATER AND 0.75" HOT WATER RETURN CONTINUED ON MEZZANINE PLAN.
13. 2 PSI GAS RISER FROM SERVICE. PROVIDE ANODELESS RISER, VALVES AND REGULATOR PER DETAIL SHEET P4.3.
14. NATURAL GAS PIPING RUN IN ATTIC SPACE.
15. NATURAL GAS PIPING CONTINUED ON MEZZANINE PLAN.
16. PIPING UNDER MEZZANINE FLOOR ABOVE.
17. OIL INTERCEPTOR. SEE FOUNDATION PLAN.
18. LIFT STATION. SEE CIVIL ENGINEERING DRAWINGS.
19. COMMERCIAL 60# WASHER BY OWNER. SEE P3.1.
20. EMERGENCY GENERATOR NATURAL GAS REGULATOR. 2 PSI INLET PRESSURE, 11" W.C. OUTLET PRESSURE, 1965 CFH FLOW. SEE DETAIL SHEET P4.3.

STORM SHELTER NOTES


PENETRATIONS THROUGH THE STORM SHELTER ENVELOPE LARGER THAN 3-1/2 SQUARE INCHES IN AREA FOR RECTANGULAR OPENINGS OR 2-1/16" IN DIAMETER SHALL BE CONSIDERED OPENING AND SHALL BE PROVIDED WITH AN OPENING PROTECTIVE DEVICE. REFERENCE STRUCTURAL DRAWINGS.

WATER NOTE
SHELTER CAPACITY IS 13 PEOPLE. ONE WATER CLOSET IS REQUIRED. THE LAVATORY IS NOT REQUIRED. HAND SANITIZER WILL BE STORED BY THE OWNER.
BASED ON 3 WATER CLOSET USES PER 8HR PERIOD PER OCCUPANT (FROM L.E.D.), IN A 2 HR PERIOD THAT IS 3/4 USES PER PERSON. FOR 13 PEOPLE THAT IS 10 FLUSHES WILL BE REQUIRED. THE TANK WILL BE FILLED ON ENTRY INTO THE SPACE AS A STORM SHELTER, THE FIRE DEPARTMENT WILL NEED TO STORE ENOUGH WATER TO ACCOMMODATE 9 ADDITIONAL FLUSHES. EACH TANK FILL/FLUSH REQUIRES 1.6 GALLONS OF WATER, 1.6 GALLONS PER FLUSH X 9 = 14.4 GALLONS MINIMUM OF POTABLE WATER NEED TO BE MADE AVAILABLE FOR WATER CLOSET USAGE.
ADDITIONAL POTABLE WATER SHALL BE STORED FOR DRINKING. INCLUDE THESE REQUIREMENTS IN THE OWNER'S INSTRUCTIONS.

NAUMAN & ZELINSKI LLC.

204 S. Ludlow Street Suite 400 Dayton, Ohio 45402
Phone: (937) 223-3821 - Fax: (937) 223-3849

App Architecture
creative focused design



Beavercreek Township

Fire Station No. 65

1777 Trebin Road, Beavercreek Township, Ohio 45385

ISSUE:

NO.	DATE	DESCRIPTION
	04/03/20	FOR CONSTRUCTION

DATE 04/03/20

JOB NO. 3541.00

DRAWN DEG

CHECKED DEG

CAD 18102P2.1.dwg


COPYRIGHT © 2020 App Architecture, Inc.

TITLE


LEVEL 1
FLOOR PLAN

SHEET NO.

P2.1



MEZZANINE AND UPPER APPARATUS BAY PLAN
SCALE: 1/8" = 1'-0"



CONSTRUCTION NOTES

1. AIR HOSE REEL WITH MOUNTING BRACKET AND 50 LF OF 3/8" 300 PSI HOSE. REELCRAFT # 5650 OLP.
2. GAS-FIRED RADIANT HEATER BY H.C. VALVE AND CONNECT NATURAL GAS TO HEATER. PROVIDE FULL SIZE DIRT LEG ON DROP.
3. GAS-FIRED UNIT HEATER BY H.C. VALVE AND CONNECT NATURAL GAS TO HEATER. PROVIDE FULL SIZE DIRT LEG ON DROP.
4. GAS-FIRED FURNACE BY H.C. VALVE AND CONNECT NATURAL GAS TO HEATER. PROVIDE FULL SIZE DIRT LEG ON DROP.
5. 2" WATER (SOFT) RISER FROM WATER SERVICE ROOM BELOW.
6. DOMESTIC WATER HEATER SEE DETAIL SHEET P4.3.
7. AIR COMPRESSOR. SEE DETAIL SHEET P4.3.
8. GAS SOLENOID VALVE CONTROLLING GAS TO KITCHEN RANGE AND OUTDOOR GRILL. SEE DETAIL SHEET P4.3.
9. 0.75" DOMESTIC WATER DROP DOWN. SEE SHEET P2.1 FOR CONTINUATION.
10. DROP 2" GAS (7"W.C.) AND 2" HIGH PRESSURE GAS (2 PSI) DOWN. SEE LEVEL ONE PLAN FOR CONTINUATION.
11. SLOPE PIPING TO FOLLOW PITCH OF ROOF/STRUCTURE
12. 1.5" HUB DRAIN WITH 3" ADAPTER ON END. TOP TO BE MOUNTED APPROXIMATELY 1" ABOVE MEZZANINE FLOOR.
13. DROP PIPING TO NEAR MEZZANINE FLOOR AND OFFSET INTO SPACE BETWEEN THE BOTTOM OF THE TRUSSES AND THE FIRST FLOOR CEILING. SEE FIRST FLOOR PLAN FOR CONTINUATION.
14. PIPING INTO SPACE BETWEEN THE BOTTOM OF THE TRUSSES AND THE FIRST FLOOR CEILING. SEE FIRST FLOOR PLAN FOR CONTINUATION.
15. 3" VENT THRU ROOF.
16. 0.5" COLD WATER DOWN TO HUMIDIFIER BY H.C. PROVIDE VALVE AND ATMOSPHERIC VACUUM BREAKER (EQUAL TO WATTS # LF288A) AT 36" A.F.F. PIPING CONTINUED FOR OUTLET OF VACUUM BREAKER BY H.C.

ISSUE:

NO.	DATE	DESCRIPTION
	04/03/20	FOR CONSTRUCTION


DATE	04/03/20
JOB NO.	3541.00
DRAWN	DEG
CHECKED	DEG
CAD	18102P2.2.dwg

COPYRIGHT © 2020 App Architecture, Inc.


TITLE
MEZZANINE AND
UPPER APPARATUS
BAY PLAN

SHEET NO.


P2.2



ENLARGED KITCHEN AREA PLAN
SCALE: 1/4" = 1'-0"



ENLARGED BATHROOM AREA PLAN
SCALE: 1/4" = 1'-0"



ENLARGED EMS AND WATER SERVICE ROOMS PLAN
SCALE: 1/4" = 1'-0"

CONSTRUCTION NOTES

1. COMBINATION FIRE AND DOMESTIC WATER SERVICE BY SITE UTILITY CONTRACTOR. SEE SITE UTILITY PLAN FOR CONTINUATION.
2. FIRE SERVICE BY FIRE SUPPRESSION CONTRACTOR. SEE FIRE SUPPRESSION DRAWINGS
3. 3" DOMESTIC WATER SERVICE. SEE DETAIL SHEET P4.3.
4. DUPLEX WATER SOFTENER. SEE DETAIL SHEET P4.2.
5. 3" SANITARY DOWN AND 1.5" VENT RISER UP.
6. FREEZE-PROOF HOSE BIBB IN RECESSED BOX. WOODFORD # B65 OR APPROVED EQUAL. MOUNT APPROX. 24" A.F.F.
7. COMMERCIAL EXTRACTOR/WASHER. VALVE AND CONNECT 1" COLD AND 1" HOT WATER. PIPE 3" DISCHARGE TO TOP OF DRAIN TROUGH. PROVIDE A PDI "B" WATER HAMMER ARRESTOR ON BOTH COLD AND HOT WATER SUPPLIES.
8. DRAIN TROUGH WITH LINT TRAP 48"x18"x12" H. H-M COMPANY OR APPROVED EQUAL. PROVIDE 3" INLET FOR COMMERCIAL WASHER AND 3" STAND PIPE FOR ADJACENT FRONT LOAD WASHER IN BACK OF TRAP LID. RECESS FLUSH WITH 4" WASHER CONCRETE PAD.
9. UNDER COUNTER ICE MACHINE. VALVE AND CONNECT COLD WATER. PIPE DISCHARGE TO FLOOR DRAIN.
10. COUNTERTOP COFFEE MACHINE. VALVE AND CONNECT RO WATER.
11. UNDER COUNTER RESIDENTIAL DISHWASHER. CONNECT TO HOT WATER AND WASTE FROM ADJACENT SINK.
12. 1.5" HUB DRAIN WITH 2" ADAPTER FOR ICE MAKER DRAIN. CENTER DRAIN IN OPENING FOR ICE MAKER AND KEEP 2" ADAPTER TIGHT TO WALL. TERMINATE APPROXIMATELY 1" ABOVE FINISHED FLOOR TO MAINTAIN 2" AIR GAP
13. DROP 1" GAS DOWN IN WALL AND OFFSET IN KNEE WALL TO THE RANGE.
14. GAS RANGE. VALVE AND CONNECT NATURAL GAS TO RANGE.
15. WATER HAMMER ARRESTOR MOUNTED ON COLD WATER PIPING ABOVE CEILING.
16. REDUCE OR COMPRESS INSULATION THRU WALL TO FIT A 2" (MAXIMUM) HOLE IN WALL. (NO OFFSET OR SHIELDING REQUIRED)
17. DROP GAS PIPING INTO GROUND EXTEND PIPING TO EMERGENCY GENERATOR. PROVIDE ANODELESS RISER. SEE DETAIL SHEET P4.3.
18. 1.5" NATURAL GAS (2 PSI) FROM MEZZANINE ABOVE. SEE DRAWING P2.2.
19. DROP 0.5" COLD WATER, 0.5" HOT WATER AND 0.5" RO WATER PIPING DOWN IN WALL AND OFFSET HORIZONTALLY IN "PONY" WALL TO SERVE KITCHEN SINK.
20. VALVE AND CAP 0.75" GAS (@ 2 PSI) FOR FUTRE REGULATOR AND EXTENSION TO DRYER IN DECONTAM. ROOM.

App Architecture
creative focused design



Beavercreek Township
Fire Station No. 65
1777 Trebin Road, Beavercreek Township, Ohio 45385

ISSUE:		
NO.	DATE	DESCRIPTION
	04/03/20	FOR CONSTRUCTION


DATE	04/03/20
JOB NO.	3541.00
DRAWN	DEG
CHECKED	DEG
CAD	18102P3.1.dwg

TITLE
ENLARGED PLANS


SHEET NO.

P3.1


NAUMAN & ZELINSKI LLC.
204 S. Ludlow Street Suite 400 Dayton, Ohio 45402
Phone: (937) 223-3821 - Fax: (937) 223-3849



C1 GAS REGULATOR AND SOLENOID VALVE DETAIL
N.T.S.




F1 DOMESTIC WATER HEATER
N.T.S.




C3 NATURAL GAS CONNECTIONS DETAIL
N.T.S.


- 1 DRAIN VALVE. PIPE DISCHARGE TO FLOOR DRAIN.
- 2 SAFETY T&P RELIEF VALVE. PIPE DISCHARGE TO FLOOR DRAIN.
- 3 THERMOMETER. (TYPICAL)
- 4 120V POWER BY E.C.
- 5 PRESSURE RELIEF VALVE PROVIDED WITH DOMESTIC WATER HEATER. PIPE DISCHARGE TO FLOOR DRAIN.
- 6 IMMERSION AQUASTAT TO CONTROL CIRCULATION PUMP.
- 7 BALANCING VALVE. WATER HEATER MANUFACTURER'S REPRESENTATIVE SHALL BALANCE VALVES AS REQUIRED DURING FACTORY START-UP.
- 8 CIRCULATION PUMP CONTROLLED BY AQUASTAT IN TANK.
- 9 EXPANSION TANK AMTROL # ST-30V-C OR EQUAL BY WATTS OR WESSELS.
- 10 4" CONCRETE PAD BY GENERAL TRADES.
- 11 7 DAY PROGRAMABLE TIME CLOCK



C5 GAS SERVICE SCHEMATIC
N.T.S.



D5 DOMESTIC WATER SERVICE
N.T.S.



F5 COMPRESSED AIR SYSTEM SCHEMATIC
N.T.S.

GAS LOADS	
ITEM	LOAD
APPARATUS BAY EQUIPMENT	
RADIANT HEATER RH-1	80 CFH
RADIANT HEATER RH-2	80 CFH
RADIANT HEATER RH-3	150 CFH
RADIANT HEATER RH-4	80 CFH
UNIT HEATER UH-1	200 CFH
	590 CFH
MEZZANINE EQUIPMENT	
FURNACE F-1	80 CFH
FURNACE F-2	60 CFH
FURNACE F-3	80 CFH
FURNACE F-4	100 CFH
FURNACE F-5	100 CFH
WATER HEATER	100 CFH
GAS DRYER	0 CFH
T.O.G. GAS DRYER	30 CFH
KITCHEN RANGE	60 CFH
OUTDOOR GRILL	75 CFH
	685 CFH
FUTURE GAS DRYER	135 CFH
EM GENERATOR. @ 11" W.C.	1,965 CFH
SERVICE TOTAL	3,375 CFH

- WH1 WATER HEATER #1, GAS FIRED. STORAGE - 20 GALLONS NOM. RECOVERY - 110 GPH @ 90° RISE INPUT - 100,000 CFH GAS PRESSURE - 7" W.C. HEAT EXCHANGER - 316 STAINLESS STEEL BASIS OF DESIGN - HTP # RGH-20-100F OR APPROVED EQUAL.
- RCP1 HOT WATER RECIRC. PUMP #1 CAPACITY - 1 GPM @ 10 FT. HD. ELECTRICAL - 120V/1PH 1/12 HP. BASIS OF DESIGN - B&G # ECOCIRC XL, 104450LF 6050B2004LF OR APPROVED EQUAL.
- HWS1 HOT WATER STORAGE TANK #1 STORAGE CAPACITY - 60 GALLONS TANK MATERIAL - 316 STAINLESS STEEL INSULATION - 2" CFC FREE FOAM W/ OUTER SHELL STAINLESS STEEL CONTROL WELL FOR AQUASTAT
- CP1 HOT WATER CIRC. PUMP #1 CAPACITY - 2 GPM @ 6 FT. HD. ELECTRICAL - 120V/1PH 60 WATTS MAX BASIS OF DESIGN - B&G # ECOCIRC 19-16 6050B2004LF OR APPROVED EQUAL.

NAUMAN & ZELINSKI LLC.
204 S. Ludlow Street Suite 400 Dayton, Ohio 45402
Phone: (937) 223-3821 - Fax: (937) 223-3849

App Architecture
creative focused design
615 Woodside Drive, Englewood, Ohio 45322
T 937.836.8698 F 937.832.3696
www.app-arch.com




Beavercreek Township
Fire Station No. 65
1777 Trebbin Road, Beavercreek Township, Ohio 45385

ISSUE:		
NO.	DATE	DESCRIPTION
	04/03/20	FOR CONSTRUCTION

DATE	04/03/20
JOB NO.	3541.00
DRAWN	DEG
CHECKED	DEG
CAD	18102P4.dwg
COPYRIGHT © 2020 App Architecture, Inc.	
TITLE	
DETAILS	

SHEET NO.
P4.3



ISSUE:		
NO.	DATE	DESCRIPTION
	04/03/20	FOR CONSTRUCTION

DATE	04/03/20
JOB NO.	3541.00
DRAWN	DEG
CHECKED	DEG
CAD	18102P5-1.dwg

COPYRIGHT © 2020 App Architecture, Inc.

TITLE
**SOIL, WASTE, &
VENT DIAGRAM**

SHEET NO.

P5.1

1

2

3

4

5

6

7

SEISMIC CONTROL SPECIFICATIONS

PART 1 – GENERAL

1.1 SUMMARY

A. THIS SECTION INCLUDES THE FOLLOWING:

1. SEISMIC CONTROL REQUIREMENTS.

1.2 PERFORMANCE REQUIREMENTS

A. SEISMIC CERTIFICATION AND ANALYSIS

1. THE CONTRACTOR SHALL RETAIN A SPECIALTY CONSULTANT OR EQUIPMENT MANUFACTURER TO DEVELOP A SEISMIC RESTRAINT SYSTEM AND PERFORM SEISMIC CALCULATIONS IN ACCORDANCE WITH THE OBC AND ASCE 7, AND ADDITIONAL REQUIREMENTS SPECIFIED IN THIS SECTION. A PROFESSIONAL ENGINEER EXPERIENCED IN SEISMIC RESTRAINT DESIGN AND INSTALLATION AND LICENSED IN THE STATE OF OHIO SHALL BE RESPONSIBLE FOR CALCULATIONS, RESTRAINT SELECTIONS AND INSTALLATION DETAILS.

2. THE SEISMIC RESTRAINT DESIGN SHALL CLEARLY INDICATE THE ATTACHMENT POINTS TO THE BUILDING STRUCTURE AND DESIGN FORCES IN ALL HORIZONTAL AND VERTICAL AXES AT THE ATTACHMENT POINTS. THE SEISMIC RESTRAINT ENGINEER SHALL COORDINATE ALL ATTACHMENTS WITH THE BUILDING'S STRUCTURAL ENGINEER OF RECORD, WHO SHALL VERIFY THE ATTACHMENT METHODS AND THE ABILITY OF THE BUILDING STRUCTURE TO ACCEPT THE LOADS IMPOSED.

3. THE SEISMIC RESTRAINT DESIGN SHALL BE BASED ON ACTUAL EQUIPMENT DATA (DIMENSIONS, WEIGHT, CENTER OF GRAVITY, ETC.) OBTAINED FROM SUBMITTALS OR THE MANUFACTURERS. THE EQUIPMENT MANUFACTURER SHALL VERIFY THAT THE ATTACHMENT POINTS ON THE EQUIPMENT CAN ACCEPT THE COMBINATION OF SEISMIC, WEIGHT, AND OTHER LOADS IMPOSED. FOR LIFE SAFETY SYSTEMS AND OTHER SYSTEMS THAT MUST REMAIN OPERATIONAL DURING AND AFTER AN EARTHQUAKE, THE MANUFACTURER SHALL PROVIDE CERTIFICATION THAT THE EQUIPMENT CAN ACCEPT THE LOADS IMPOSED AND REMAIN OPERATIONAL.

4. ANALYSIS SHALL INCLUDE CALCULATED DEAD LOADS, STATIC SEISMIC LOADS, AND CAPACITY OF MATERIALS UTILIZED FOR THE CONNECTION OF THE EQUIPMENT OR SYSTEM TO THE STRUCTURE. ANALYSIS SHALL DETAIL ANCHORING METHODS, BOLT DIAMETER, EMBEDMENT AND/OR WELDED LENGTH. ALL SEISMIC RESTRAINT DEVICES SHALL BE DESIGNED TO ACCEPT, WITHOUT FAILURE, THE FORCES DETAILED IN THE CODE ACTING THROUGH THE EQUIPMENT OR SYSTEM'S CENTER OF GRAVITY.

1.3 SUBMITTALS

A. DELEGATED–DESIGN SUBMITTAL: THE SEISMIC RESTRAINT DESIGN, CONSISTING OF CALCULATIONS, RESTRAINT SELECTION, INSTALLATION DETAILS, AND OTHER DOCUMENTATION, SHALL BE SUBMITTED. THIS SUBMITTAL SHALL BE SIGNED AND SEALED BY A PROFESSIONAL ENGINEER, AS STATED ABOVE. THIS SUBMITTAL WILL BECOME PART OF THE PROJECT DESIGN CALCULATIONS, INCLUDED IN THE PROJECT RECORDS, AND WHEN REQUIRED, WILL BE SUBMITTED TO THE AUTHORITY HAVING JURISDICTION.

B. SEISMIC RESTRAINT DEVICES: PRODUCT DATA, VERIFICATION OF SEISMIC CAPABILITIES AND INSTALLATION DETAILS.

C. WELDING CERTIFICATES.

D. FIELD QUALITY–CONTROL TEST REPORTS.

1.4 QUALITY ASSURANCE

A. COMPLY WITH SEISMIC–RESTRAINT REQUIREMENTS IN THE OBC UNLESS REQUIREMENTS IN THIS SECTION ARE MORE STRINGENT.

B. WELDING: QUALIFY PROCEDURES AND PERSONNEL ACCORDING TO AWS D1.1/D1.1M, "STRUCTURAL WELDING CODE – STEEL."

C. ALL SEISMIC RESTRAINTS AND COMBINATION ISOLATOR / RESTRAINTS SHALL HAVE VERIFICATION OF THEIR SEISMIC CAPABILITIES. MANUFACTURERS MAY VERIFY THEIR CAPABILITIES BY TESTING THAT IS WITNESSED BY AN INDEPENDENT PROFESSIONAL ENGINEER OR AN ASSOCIATION THAT HAS DEVELOPED A UNIFORM SET OF TEST STANDARDS. INDEPENDENT APPROVAL CAN ALSO BE OBTAINED BY AGENCIES SUCH AS OSHPD (OFFICE OF STATEWIDE HEALTH, PLANNING AND DEVELOPMENT) FROM THE STATE OF CALIFORNIA, NES, ICBO ES, FACTORY MUTUAL, UNDERWRITERS LAB, RECOGNIZED INDUSTRY STANDARDS ORGANIZATIONS SUCH AS VISCMA, ETC.

PART 2 – PRODUCTS

2.1 SEISMIC–RESTRAINT DEVICES

A. SEISMIC RESTRAINT DEVICES MAY INCLUDE ANY MANUFACTURER'S SYSTEM(S) SUITABLE FOR THE BUILDING CONSTRUCTION APPLICATION.

B. MANUFACTURERS: SUBJECT TO COMPLIANCE WITH REQUIREMENTS, PROVIDE PRODUCTS BY ONE OF THE FOLLOWING:

1. THE VMC GROUP (VIBRATION MOUNTING AND CONTROLS)

2. MASON INDUSTRIES

3. KINETICS NOISE CONTROL.

SEISMIC GENERAL REQUIREMENTS

1. THE PROJECT HAS SEISMIC LOAD SUPPORT REQUIREMENTS BASED ON THE SEISMIC USE GROUP (OCCUPANCY) DESIGNATION OF THE FACILITY OF "IV" AND SEISMIC DESIGN CATEGORY "C". REFER TO DRAWING S0.01 FOR ADDITIONAL INFORMATION.

2. SEISMIC DESIGN REQUIREMENTS FOR MECHANICAL AND ELECTRICAL COMPONENTS SHALL BE PROVIDED AS REQUIRED BY 2017 OHIO BUILDING CODE CHAPTER 16, SECTION 1613 EARTHQUAKE LOADS AND BY REFERENCE, THE AMERICAN SOCIETY OF STRUCTURAL ENGINEERS (ASCE) STANDARD 7–10 "MINIMUM DESIGN LOADS FOR BUILDING AND OTHER STRUCTURES" (2010).

3. CHAPTER 13 OF ASCE 7–10 DEFINES THE REQUIREMENTS FOR THE MECHANICAL AND ELECTRICAL COMPONENTS.

4. THE COMPONENT IMPORTANCE FACTOR, Ip SHALL BE 1.5 FOR ALL COMPONENTS PER ASCE 7–10, 13.1.3 SINCE THE COMPONENTS ARE REQUIRED TO FUNCTION FOR LIFE SAFETY PURPOSES AFTER AN EARTHQUAKE AS WELL AS THE COMPONENTS ARE ALL LOCATED WITHIN AN OCCUPANCY CATEGORY "IV" STRUCTURE.

5. ASCE 7–10, TABLE 13.6–1 DEFINES THE SEISMIC AMPLIFICATION FACTOR Ap AND RESPONSE FACTOR Rp FOR EACH COMPONENT THAT SHALL BE USED IN DETERMINING THE ATTACHMENT REQUIREMENTS.

6. CERTAIN COMPONENTS TO BE SEISMICALLY BRACED AND SUPPORTED ARE TO ALSO INCLUDE VIBRATION ISOLATION WHERE INDICATED.

7. COMPONENTS OR SYSTEMS CAN BE INSTALLED IN A MANNER TO REDUCE SEISMIC BRACING OR SUPPORT REQUIREMENTS. ALL MECHANICAL AND ELECTRICAL SYSTEMS MUST FUNCTION AFTER AN EARTHQUAKE. EQUIPMENT, COMPONENTS, PIPING, DUCTWORK, CONDUIT, COMMUNICATION CABLING, ETC. SHALL BE SEISMICALLY BRACED. GENERAL GUIDELINES OR APPROACH FOR PROJECT SYSTEMS:

A. DUCTWORK IS DESIGNED TO BE LESS THAN 6 SQ. FT., NO SEISMIC BRACING.

B. PIPING SHOULD BE HUNG TIGHT TO STRUCTURE WITH THREADED ROD LESS THAN 12", NO SEISMIC BRACING IF INSTALLED IN THIS MANNER.

C. HVAC SYSTEMS IN–LINE WITH DUCT SYSTEM (FANS, HUMIDIFIERS) ARE LESS THAN 75 LBS., NO SEISMIC BRACING.

D. FLOOR OR GRADE SET EQUIPMENT, TO BE ANCHORED TO EQUIPMENT PAD AND IN TURN SECURED TO THE FLOOR.

E. FIRE SUPPRESSION PIPING SHALL SEISMIC BRACED PER THE REQUIREMENTS OF NFPA 13.

F. FLOOR/WALL MOUNTED ELECTRICAL EQUIPMENT, PANELBOARDS, AUTOMATIC TRANSFER SWITCHES, ETC. SHALL BE SEISMICALLY BRACED/SUPPORTED.

G. LIGHTING FIXTURES SHALL BE SUPPORTED INDEPENDENTLY OF SUSPENDED CEILING SYSTEMS.

H. CEILING FANS SHALL BE SEISMICALLY BRACED/SUPPORTED.

I. CONDUITS 2.5" AND LARGER SHALL BE SEISMICALLY BRACED/SUPPORTED.

GENERAL NOTES

1. PROVIDE COMPLETE AND FUNCTIONAL HVAC SYSTEMS PER HVAC PLANS INCLUDING FURNISHING, INSTALLING, TESTING AND WARRANTY OF ALL WORK.

2. WORK SHALL BE IN ACCORDANCE WITH THE 2017 OHIO BUILDING AND MECHANICAL CODES INCLUDING REFERENCED CODES AND STANDARDS, ALL FEDERAL, STATE, AND LOCAL CODES AND ALL APPLICABLE LAWS, ORDINANCES AND REGULATIONS.

3. WORK SHALL BE PERFORMED USING BEST QUALITY INSTALLATION PRACTICE BY A QUALIFIED TRADE CONTRACTOR AND THEIR QUALIFIED SUBCONTRACTORS. ALL CONTRACTORS SHALL BE LICENSED AND BE BONDED FOR THE WORK.

4. ALL WORK SHALL BE PERFORMED IN ACCORDANCE WITH OSHA AND OWNER SAFETY STANDARDS AND PRACTICES. ALL ON SITE PERSONNEL SHALL BE SAFETY TRAINED AND OWNER CERTIFIED.

5. OBTAIN REQUIRED PERMITS RELATED TO THE WORK AND PAY ALL PERMIT AND INSPECTION FEES.

6. THE AUTHORITY HAVING JURISDICTION SHALL INSPECT AND APPROVE ALL WORK. PROVIDE A FINAL CERTIFICATE OF APPROVAL FROM THE AUTHORITY HAVING JURISDICTION AND PRESENT TO THE OWNER BEFORE REQUESTING FINAL PAYMENT AND RELEASE OF RETAINAGE.

7. ALL EQUIPMENT AND MATERIAL REQUIRED FOR COMPLETE AND FUNCTIONAL HVAC SYSTEMS ARE INCLUDED IN THE CONTRACT.

GENERAL REQUIREMENTS

1. PROTECT ALL FURNISHED MATERIAL AND EQUIPMENT FROM THEFT AND DETERIORATION OR CONTAMINATION DUE TO WEATHER OR CONSTRUCTION ACTIVITIES.

2. PROTECT OWNERS PROPERTY AND PROPERTY OF OTHER CONTRACTORS.

3. REMOVE ALL CONSTRUCTION DEBRIS FROM SITE. RECYCLE DEBRIS WHERE POSSIBLE. DISPOSE OF ALL HAZARDOUS MATERIAL IN ACCORDANCE WITH ENVIRONMENTAL LAWS.

4. PROVIDE ALL CUTTING AND PATCHING REQUIRED TO INSTALL MATERIAL AND EQUIPMENT.

5. EXISTING ROOF PATCHING SHALL BE SUBCONTRACTED TO A BONDED ROOFING CONTRACTOR FAMILIAR WITH THE ROOFING SYSTEM. MAINTAIN ANY REMAINING ROOF WARRANTY.

6. PROVIDE APPROPRIATE FIRESTOPPING SYSTEM FOR ANNULAR SPACE OPENINGS AROUND DUCT AND PIPE PENETRATIONS THROUGH FIRE RESISTANCE RATED CONSTRUCTION. ANNULAR SPACE OPENINGS AT DUCT OR PIPE PENETRATIONS IN NON RATED CONSTRUCTION TO BE CLOSED AIR AND WATER TIGHT.

7. MATERIALS AND EQUIPMENT SHALL BE ONE OF THE BRAND OR MANUFACTURERS LISTED OR AN APPROVED EQUAL.

8. ELECTRONIC SHOP DRAWINGS SHALL BE PROVIDED IN .PDF FORMAT FOR THE ENGINEER'S APPROVAL FOR ALL MATERIALS AND EQUIPMENT. SHOP DRAWINGS SHALL BE SPECIFICALLY EDITED TO ELIMINATE SUPERFLUOUS INFORMATION AND SHALL CLEARLY SHOW SPECIFICS FOR THE MATERIAL AND EQUIPMENT PROVIDED.

9. COORDINATE INSTALLATION OF ACTUAL EQUIPMENT AND SYSTEMS PROVIDED WITH OTHER TRADES AND NEW OR EXISTING CONDITIONS.

10. PROJECT CONDITIONS REQUIRE COORDINATION TO MAKE SYSTEMS FIT IN THE AVAILABLE SPACE. HVAC CONTRACTOR SHALL PROVIDE AN INITIAL ¼"=10" SET OF DRAWINGS AND DISTRIBUTED TO OTHER TRADE CONTRACTORS FOR COORDINATION. ALL CONTRACTORS SHALL COOPERATE TO MODIFY THEIR RESPECTIVE MATERIAL AND EQUIPMENT INSTALLATION AND DEPICT ON A DETAILED, FINISHED COORDINATION SET OF DRAWINGS BEFORE INSTALLATION. ALLOW FOR EXPECTED MINOR OFFSETS OR RELOCATION SYSTEM OR EQUIPMENT WITHOUT REQUEST FOR COMPENSATION ADJUSTMENT.

11. PROVIDE FINAL COORDINATION/INSTALLATION DRAWINGS TO THE OWNER IN BOUND PAPER AS WELL AS ELECTRONIC FORMAT FOR RECORD.

12. INSTALL ALL MATERIALS AND EQUIPMENT IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS AND REQUIREMENTS.

13. INSTALL ALL MATERIAL AND EQUIPMENT TO PROVIDE REQUIRED CLEARANCES TO MEET CODE REQUIREMENTS, MANUFACTURER'S RECOMMENDATIONS AND MAINTENANCE SERVICE.

14. ALL WORK AREAS SHALL BE CLEANED TO MATCH ORIGINAL CONDITION.

15. PROVIDE TESTING, ADJUSTING AND BALANCING (TAB) REPORTS FOR AIR AND WATER SYSTEMS. A CERTIFIED AABC OR NEBB FIRM SHALL PROVIDE THE BALANCE.

16. MAINTAIN RECORD DRAWINGS AND PROVIDE TO THE OWNER OR HIS AGENT.

17. PROVIDE TWO (2) BOUND, PAPER COPIES OF ALL OPERATING AND MAINTENANCE MANUALS. PROVIDE AN ELECTRONIC COPY OF THE OPERATING AND MAINTENANCE MANUAL.

18. PROVIDE WARRANTY FOR ALL WORKMANSHIP, EQUIPMENT AND MATERIAL. WARRANTY SHALL BE 1 YEAR FOR PART AND LABOR, PROVIDE EXTENDED WARRANTY PERIOD FOR PARTS AND/OR LABOR AS IDENTIFIED OR AS STANDARD FOR CERTAIN ITEMS OF EQUIPMENT.

19. PROVIDE TRAINING AND MAINTENANCE INSTRUCTION FOR SYSTEMS AND EQUIPMENT TO THE OWNER. TRAINING SHALL BE 16 HOURS OF TIME WITH MAXIMUM TRAINING PERIOD OF 4 HOURS.

GENERAL LEGEND

EC ELECTRICAL CONTRACTOR.

FC FIRE PROTECTION CONTRACTOR.

GC GENERAL CONTRACTOR.

HC HVAC CONTRACTOR.

PC PLUMBING CONTRACTOR.

3

NOTE SYMBOL – APPLIES ONLY TO SHEET ON WHICH IS SHOWN.

2

DETAIL NOTE SYMBOL – APPLIES ONLY TO DETAIL ON WHICH IS SHOWN.

H-1

EQUIPMENT REFERENCE SYMBOL. ELECTRICAL CONNECTION REQUIRED.

H-1

EQUIPMENT REFERENCE SYMBOL. NO ELECTRICAL CONNECTION REQUIRED.

2
H4.3

DETAIL SYMBOL
DETAIL "2" SHOWN ON SHEET H4.3.

1
H3.1

SECTION SYMBOL
SECTION "1" DESIGNATION, SHOWN ON SHEET H3.1.

1 HOUR FIRE PROTECTION
SEE SPECIFICATION FOR PENETRATION DETAILS.

2 HOUR FIRE PROTECTION
SEE SPECIFICATION FOR PENETRATION DETAILS.

3 HOUR FIRE PROTECTION
SEE SPECIFICATION FOR PENETRATION DETAILS.

DUCTWORK LEGEND

20/12 SA

RECTANGULAR DUCT
FIRST FIGURE IS SIDE SHOWN
SA – INDICATES SUPPLY AIR

10"ø RA

ROUND DUCT
DIAMETER INDICATED
RA – INDICATES RETURN AIR

|||

INSULATED FLEXIBLE DUCT

R

CHANGE OF ELEVATION
R = RISE, D = DROP

ELBOW WITH TURNING VANES

20/12

ROUND RUNOUT DUCT TAP TO RECTANGULAR DUCT WITH SPIN-IN FITTING, SEE DETAIL

10"ø

ROUND RUNOUT DUCT FITTING IN ROUND DUCT MAIN

VOLUME DAMPER

FD

FIRE DAMPER

SUPPLY DUCT SECTION – RISE, DROP

RETURN DUCT SECTION – RISE, DROP

S1–8"
300

SUPPLY AIR DEVICE S1
SEE SCHEDULE AND DETAIL
8" = NECK SIZE
300 = REQUIRED AIR FLOW (CFM)

RT

TRANSFER/RETURN AIR DEVICE WITH PLENUM BOX ABOVE
24"x24" WITH PLENUM
R1 DEVICE TAG, SEE SCHEDULE AND DETAIL

R2

TRANSFER/RETURN AIR DEVICE WITH PLENUM BOX ABOVE
24"x12" WITH PLENUM
R1 DEVICE TAG, SEE SCHEDULE AND DETAIL

R1–10"
250

RETURN/EXHAUST/TRANSFER GRILLE R1 WITH PLENUM BOX ABOVE
R1 = DEVICE TAG, SEE SCHEDULE AND DETAIL
10" = RUNOUT SIZE
250 = REQUIRED AIR FLOW (CFM)
DEVICE SIZE AS DEPICTED ON DRAWINGS OR AS INDICATED IN AIR DEVICE SCHEDULE

S2–24/12
300–8'6"

SIDEWALL AIR DEVICE
SEE AIR DEVICE SCHEDULE
24/12 = DEVICE SIZE
300 = AIR FLOW (CFM)
8'6" = MOUNTING HEIGHT (AFF)

1

ROOM TEMPERATURE SENSOR

NAUMAN & ZELINSKI LLC.

204 S. Ludlow Street Suite 400 Dayton, Ohio 45402

Phone: (937) 223-3821 • Fax: (937) 223-3849

App Architecture
creative focused design

615 Woodside Drive, Englewood, Ohio 45322
T 937.836.8898 F 937.832.3696
www.app-arch.com


STATE OF OHIO
JEFFREY D. ZELINSKI
63822
REGISTERED
PROFESSIONAL ENGINEER

Beavercreek Township
Fire Station No. 65
1777 Trebain Road, Beavercreek Township, Ohio 45385

ISSUE:
NO. DATE DESCRIPTION
04/03/20 FOR CONSTRUCTION

DATE 04/03/20
JOB NO. 3541.00
DRAWN RAD
CHECKED RAS
CAD 18102H0.1
COPYRIGHT © 2020 App Architecture, Inc.
TITLE
LEGEND & SCHEDULES
SHEET NO.

H0.1



STORM SHELTER NOTE

PENETRATIONS THROUGH THE STORM SHELTER ENVELOPE LARGER THAN 3-1/2 IN. IN AREA FOR RECTANGULAR OPENINGS OR 2-1/16" IN DIAMETER SHALL BE CONSIDERED OPENING AND SHALL BE PROVIDED WITH AN OPENING PROTECTIVE DEVICE. REFERENCE STRUCTURAL DRAWINGS.


STORM SHELTER VENTILATION NOTE:

STORM SHELTER OCCUPANCY IS 13 PEOPLE. VENTILATION OPENING REQUIREMENTS ARE 5 IN² PER OCCUPANT, SO TOTAL OF 65 IN² TOTAL. GREATER THAN 2 3/8" S (>43 IN²) OF THE AREA IS TO BE HIGH AND GREATER THAN 1 1/4" (>17 IN²) OF THE AREA IS TO BE LOW. 80 IN² PROVIDED HIGH (10"x8" OPENING WITH TYPE "A" FIRE DAMPER). 22.5 IN² PROVIDED LOW (THROUGH 5/8" UNDERCUT OF 36" WIDE DOOR).

NOTE:

FIRE DAMPERS FOR DORM ROOMS ARE NOT REQUIRED PER 2017 OBC SECTION 717.5.4 FIRE PARTITIONS EXCEPTION 4. BUILDING IS FULLY SPRINKLERED. HVAC SYSTEM IS FULLY DUCTED. DUCTWORK IS NO. 26 GAGE OR THICKER.

- CONSTRUCTION NOTES**
- HOOD BY H.C. CONNECT TO TOP OF HOOD - TRANSITION TO SIZE INDICATED ON PLAN. SLOPE DUCT BACK TOWARDS HOOD MINIMUM 1/8 INCH PER FOOT.
 - SUPPLY AIR DUCT UNDERNEATH RETURN DUCT.
 - SUPPLY AIR DUCT DOWN FROM MEZZANINE, SEE SHEET H2.2 FOR DUCT CONTINUATION.
 - RETURN AIR DUCT UP TO MEZZANINE. SEE SHEET H2.2 FOR DUCT CONTINUATION.
 - EXHAUST AIR DUCT UP TO MEZZANINE, SEE SHEET H2.2 FOR DUCT CONTINUATION.
 - CARBON MONOXIDE AND NITRIC OXIDE MONITORING PANEL. PANEL TO HAVE EIGHT (8) DISPLAY READOUTS AND AUDIO VISUAL ALARM. PROVIDE SEPARATE HORN/STROBE ALARM AND WIRE CONTROL PANEL TO ALARM WHEN ANY CO LEVEL > 50 PPM (ADJ.) AND ANY NO_x LEVEL > 30 PPM (ADJ.).
 - CARBON MONOXIDE AND NITRIC OXIDE SENSOR. MOUNT SENSOR AT 4' AFF AND 12' AFF. WIRE TO CONTROL PANEL. PANEL TO DISPLAY NITRIC OXIDE AND CARBON MONOXIDE VALUE FOR EACH SENSOR.
 - EF-2, RH-1,2,3,4 DISENGAGE OVERRIDE PUSH BUTTON.
 - EF-2 OVERRIDE ENGAGE PUSH BUTTON 30 MIN (ADJ.)
 - G.C. TO WELD 1/4" GALVANIZED STEEL IN I-BEAM TO CREATE CAVITY FOR EXHAUST AIR PATH. I-BEAM TO BE OPEN 18" AFF. G.C. TO CREATE 10" DIA. BELLMOUTH DUCT OPENING NEAR TOP OF I-BEAM. H.C. TO CONNECT TO 10" DIA. STUB OUT.
 - 10/10 S.S. EXHAUST DUCT OVER TO EF-1. PROVIDE HINGED ACCESS DOOR ON BOTH SIDES OF FAN (NEAR BOTTOM) FOR DUCT CLEANING.
 - PROVIDE SWITCH TO CONTROL FAN (WIRED BY E.C.). PROVIDE TEMPERATURE SENSOR IN HOOD WHICH WILL AUTOMATICALLY START EF-1 (REMOTE KITCHEN EF) WHEN TEMPERATURE EXCEEDS 125 DEG. F (ADJ.).
 - SEE SHEET H2.2 FOR APPARATUS BAY HVAC EQUIPMENT.
 - 8" WIDE x 6" HIGH OPENING FOR DUCT PENETRATION WITH TYPE "A", 3 HR FIRE DAMPER IN WALL.
 - 10" WIDE x 8" HIGH OPENING. 88" TO BOTTOM OF OPENING WITH TYPE "A", 3 HR FIRE DAMPER IN WALL.
 - G.C. TO PROVIDE SHROUD AROUND WALL OPENING.
 - DRYER VENT EXHAUST. TERMINATE ON EXTERIOR WALL AT 45° WITH BIRD SCREEN.
 - HUMIDISTAT.
 - WELDED S.S. DUCT W/FIRE WRAP. SLOPE MINIMUM 1/8" PER FOOT BACK TOWARDS HOOD.
 - ROUTE 0.75" CONDENSATE PIPING TO FLOOR DRAIN.
 - REFRIGERANT LINE SET. INSULATE PER MANUFACTURER'S RECOMMENDATIONS.
 - RUN REFRIGERANT PIPING MINIMUM 8 FT. A.F.F.
 - DEHUMIDIFIER - DESERT AIRE MODEL 120 OR EQUAL. 6.8 LBS/HR CAPACITY, 400 CFM, 13.8 FLA/115V/1 PH. CORD AND PLUG. PROVIDE WITH WALL MOUNTING BRACKETS. 150 LBS. EXTEND CONDENSATE TUBE TO LOCAL FLOOR DRAIN.




ISSUE:		
NO.	DATE	DESCRIPTION
1	04/03/2020	FOR CONSTRUCTION

DATE	04/03/2020
JOB NO.	3541.00
DRAWN	RAS
CHECKED	JDZ
CAD	-

TITLE
LEVEL 1 FLOOR PLAN

SHEET NO.
H2.1



- # CONSTRUCTION NOTES
1.

LOUVER BY G.C.
2.

(2) 42"W x 30"H DUCTS W/2" INSULATION. CONNECT TO LOUVER. PROVIDE 18 GA. GALVANIZED SHEET METAL WITH 2" INSULATION BLANK OFF PANELS OVER UNUSED LOUVER AREA.
3.

100"WIDE x 30"HIGH x 36"DEEP, 2" INSULATED PLENUM. PROVIDE 0.75" DRAIN LINE W/1" INSULATION TO FLOOR DRAIN.
4.

AUTO CONTROL DAMPER - INTERLOCK WITH EXHAUST FAN EF-2 VFD. PROVIDE RELAY WIRING FROM CONTACT TO VFD TO CONTROL DAMPER.
5.

DUCT OPEN TO ROOM
6.

BALANCE DAMPER. BALANCE TO CFM INDICATED ON PLAN.
7.

EXHAUST AIR CAVITY IN I-BEAM WITH 1/4" GALVANIZED STEEL PLATE. SEE DETAIL 2, SHEET H3.1 FOR DESCRIPTION.
8.

CARBON MONOXIDE AND NITRIC OXIDE MONITORING PANEL. PANEL TO HAVE EIGHT (8) DISPLAY READOUTS AND AUDIO VISUAL ALARM. PROVIDE SEPARATE HORN/STROBE ALARM AND WIRE CONTROL PANEL TO ALARM WHEN ANY CO LEVEL > 50 PPM (ADJ.) AND ANY NO₂ LEVEL > 30 PPM (ADJ.).
9.

CARBON MONOXIDE AND NITRIC OXIDE SENSOR. MOUNT SENSOR AT 4' AFF AND 12' AFF. WIRE TO CONTROL PANEL. PANEL TO DISPLAY NITRIC OXIDE AND CARBON MONOXIDE VALUE FOR EACH SENSOR.
10.

EF-2. RH-1,2,3,4 DISENGAGE OVERRIDE PUSH BUTTON.
11.

EF-2 OVERRIDE ENGAGE PUSH BUTTON 30 MIN (ADJ.).
12.

AUTO CONTROL DAMPER - INTERLOCK WITH ENERGY RECOVERY UNIT ERV-1. PROVIDE RELAY WIRING FROM ERV-1 TO CONTROL DAMPER.
13.

OUTSIDE AIR BALANCE DAMPER. BALANCE TO CFM INDICATED ON PLAN.
14.

SUPPLY DUCT UNDERNEATH RETURN DUCT.
15.

SEE FIRST FLOOR PLAN, SHEET H2.1 FOR DUCT CONTINUATION.
16.

0.75" CONDENSATE DRAIN. PIPE TO FLOOR DRAIN AND TERMINATE.
17.

EXHAUST DUCT DOWN TO FIRST FLOOR. SEE SHEET H2.1 FOR CONTINUATION.
18.

PROVIDE SIDE SHIELD DEFLECTOR PLATE TO PROJECT HEAT AWAY FROM WALL.
19.

0.75" CONDENSATE DRAIN. PIPE TO HUB DRAIN AND TERMINATE.
20.

PROVIDE HUMIDIFIER PER DETAIL.
21.

PROVIDE SIDE SHIELD DEFLECTOR PLATE TO PROJECT HEAT AWAY FROM AIR HOSE REEL/ELECTRIC CORD REEL. COORDINATE PLATE LOCATION WITH HOSE & CORD REEL LOCATIONS.
22.

AIR HOSE REEL. COORDINATE LOCATION WITH P.C. AND OWNER.
23.

ELECTRIC CORD REEL. COORDINATE LOCATION WITH E.C. AND OWNER.
24.

18"x8", 16 GA. GALVANIZED WELDED DUCT DROP DOWN TO 18" A.F.F. AND TERMINATE.
25.

REFRIGERANT LINE SET. INSULATE PER MANUFACTURER'S RECOMMENDATIONS.
26.

RUN REFRIGERANT PIPING MINIMUM 8' A.F.F.
27.

PROVIDE MOMENTARY WALL SWITCH, TURN OVER TO E.C. TO BE WIRED & LOCATED IN MASTER CONTROL PANEL, TO RUN RH-1 AND RH-2 AT 100% (ADJ.) HEAT FOR 15 MIN. (ADJ.). DOMESTIC WATER HEATER COMBUSTION AIR INTAKE AND VENT.
28.

CONCENTRIC VENTS TO BE SPACED IN GROUPS OF TWO 4" MAX. APART. 24" APART FROM NEXT GROUP OF TWO. SEE IPEX SYSTEM 636 MULTIPLE SIDEWALL TERMINATION REQUIREMENTS FOR SPACING GUIDELINES.
29.

PROVIDE TEMPERATURE SENSOR FOR UH-1 ON UNISTRUT FRAMING IN FRONT OF OUTSIDE AIR DUCT TO SENSE OUTSIDE AIR TEMPERATURE WHEN DAMPER IS OPEN. UH-1 TO RUN WHEN TEMPERATURE SENSOR IS 40 DEG. F. OR BELOW.
30.

PROVIDE MOMENTARY WALL SWITCH, TURN OVER TO E.C. TO BE WIRED & LOCATED IN MASTER CONTROL PANEL, TO RUN RH-3 AND RH-4 AT 100% (ADJ.) HEAT FOR 15 MIN. (ADJ.). PROVIDE MOMENTARY WALL SWITCH, TURN OVER TO E.C. TO BE WIRED & LOCATED IN MASTER CONTROL PANEL, TO RUN UH-1 FOR 30 MIN. (ADJ.).
31.
32.

App Architecture

creative focused design

615 Woodside Drive, Englewood, Ohio 45322
T 937.836.8898 F 937.832.3696
www.app-arch.com

NAUMAN & ZELINSKI LLC
204 S. LUDLOW ST. COLUMBUS, OHIO 43202
Phone: 614.222.3621


BEAVERCREEK TOWNSHIP
FIRE STATION
No. 65
1777 TREBEIN ROAD
BEAVERCREEK TOWNSHIP, OHIO 45385

ISSUE:
NO. DATE DESCRIPTION
04/03/20 FOR CONSTRUCTION
20

DATE 04/03/2020
JOB NO. 3541.00
DRAWN RAS
CHECKED JDZ
CAD -
COPYRIGHT © 2018
App Architecture, Inc.

TITLE
MEZZANINE FLOOR PLAN

SHEET NO.
H2.2



- # CONSTRUCTION NOTES
1. LOUVER BY G.C.
 2. (2) 42"W x 30"H DUCTS W/2" INSULATION. CONNECT TO LOUVER. PROVIDE 18 GA. GALVANIZED SHEET METAL WITH 2" INSULATION BLANK OFF PANELS OVER UNUSED LOUVER AREA.
 3. 100"WIDE x 30"HIGH x 36"DEEP, 2" INSULATED PLENUM. PROVIDE 0.75" DRAIN LINE W/1" INSULATION TO FLOOR DRAIN.
 4. AUTO CONTROL DAMPER - INTERLOCK WITH ENERGY RECOVERY UNIT ERV-1. PROVIDE RELAY WIRING FROM ERV-1 TO CONTROL DAMPER.
 5. OUTSIDE AIR BALANCE DAMPER. BALANCE TO AIRFLOW INDICATED ON PLAN.

App Architecture
creative focused design

615 Woodside Drive, Englewood, Ohio 45322
T 937.836.8898 F 937.832.3696
www.app-arch.com



BEAVERCREEK TOWNSHIP
FIRE STATION No. 65
1777 TREBEIN ROAD
BEAVERCREEK TOWNSHIP, OHIO 45385


ISSUE:


NO.	DATE	DESCRIPTION
1	04/03/2020	FOR CONSTRUCTION


DATE	04/03/2020
JOB NO.	3541.00
DRAWN	RAS
CHECKED	JDZ
CAD	-

COPYRIGHT © 2020 App Architecture, Inc.
TITLE
HVAC SECTIONS

SHEET NO.
H3.2







A schematic diagram of a gas turbine engine. The flow path is indicated by arrows: 1 (inlet), 2 (compressor), 3 (combustor), 4 (fuel injection), 5 (turbine), 6 (exhaust), 7 (heat exchanger), 8 (secondary turbine), 9 (exhaust). The diagram is labeled with numbers 1 through 11.

- ① EXHAUST DUCT.
- ② FLEXIBLE DUCT CONNECTION VIBRATION ISOLATOR.
- ③ VIBRATION ISOLATORS.
- ④ TRANSITION TO EXHAUST FAN INLET SIZE.
- ⑤ THREADED ROD.
- ⑥ BELT GUARD.
- ⑦ ACCESS DOOR.
- ⑧ DISCHARGE DUCT IS SAME SIZE AS FAN OUTLET.
- ⑨ MOTORIZED OR GRAVITY BACK DAMPER PROVIDED WITH EXHAUST FAN.
- ⑩ STEEL CHANNEL, ATTACH TO STRUCTURE.
- ⑪ INSULATE EXTERIOR OF DUCT TO PREVENT COLD DUCT SURFACES INSIDE OF BLDG.

1 WATER HEATER BY P.C.

2 FLOOR.

3 3"Ø SCHEDULE 40 CPVC FLUE, PITCH HORIZONTAL RUNS BACK TO WATER HEATER.

4 3"Ø SCHEDULE 40 CPVC COMBUSTION AIR INTAKE. PITCH HORIZONTAL RUNS BACK TO WATER HEATER.

5 UNISTRUT SUPPORTS. ATTACH TO STRUCTURAL STEEL JOISTS. DO NOT SUPPORT FROM DECK.


6 STEEL BAND HANGER.

7 CONCENTRIC WALL VENT TERMINATION. SEE DETAIL.

- ① WATER HEATER BY P.C.
- ② FLOOR.
- ③ 3"Ø SCHEDULE 40 CPVC FLUE. PITCH HORIZONTAL RUNS BACK TO WATER HEATER.
- ④ 3"Ø SCHEDULE 40 CPVC COMBUSTION AIR INTAKE. PITCH HORIZONTAL RUNS BACK TO WATER HEATER.
- ⑤ UNISTRUT SUPPORTS. ATTACH TO STRUCTURAL STEEL JOISTS. DO NOT SUPPORT FROM DECK.
- ⑥ STEEL BAND HANGER.
- ⑦ CONCENTRIC WALL VENT TERMINATION. SEE DETAIL.

Diagram illustrating the installation of a return grille in a suspended ceiling. The diagram shows a cross-section of the ceiling structure, including the ceiling joists, the suspended ceiling grid, and the return grille. The grille is labeled with the number 1. The ceiling grid is labeled with the number 2. The return grille is shown with a flange that fits into the grid. The distance between the ceiling joists is labeled as 8". The diagram also shows the connection of the grille to the ductwork, which is labeled with the number 3. The ductwork is shown with a flange that fits into the grille. The diagram is labeled with the number 4 for the grille, 5 for the ductwork, and 6 for the ceiling grid. The text "(EXCEPT WHERE HEIGHT RESTRICTED BY EXISTING CONDITIONS)" is shown. The diagram is labeled with the number 7 for the ceiling joist, 8 for the ceiling grid, and 9 for the return grille.

- ① PLENUM – SIZE TO MATCH GRILLE. PAINT INTERIOR OF PLENUM FLAT BLACK.
- ② EXHAUST/RETURN GRILLE FRAME TO MATCH CEILING CONDITION.
- ③ SPIN-IN FITTING WITH BALANCING DAMPER, USE FOR ALL ACCESSIBLE CEILINGS.
- ④ PROVIDE REMOTE BALANCING DAMPER IN BRANCH DUCT ABOVE ACCESSIBLE CEILING FOR EACH GRILLE WHERE GRILLE IS INSTALLED ABOVE INACCESSIBLE CEILING (PREFERRED).
- ⑤ PROVIDE BALANCING DAMPER AT DEVICE ONLY WHERE DUCT MOUNTED DAMPER CANNOT BE PROVIDED DUE TO INACCESSIBLE CEILING.




- ⑥ FLEXIBLE DUCT ACCEPTABLE ABOVE ACCESSIBLE CEILING ONLY. MAX. 2 FT. REFER TO CEILING DIFFUSER DETAIL FOR INSTALLATION REQUIREMENTS.
- ⑦ SHEETMETAL DUCT.
- ⑧ SUPPORT PLENUM FROM STRUCTURE WITH DUCT STRAP HANGERS.
- ⑨ FASTEN SHEETMETAL PLENUM OR DUCT TO AIR DEVICE, EACH SIDE.
- ⑩ DUCT STRAP HANGER.

The diagram shows a cross-section of a triangular louver assembly. A central rectangular louver is shown with horizontal slats. The louver is set within a larger triangular frame. Callout 1 points to the top of the louver. Callout 2 points to the bottom of the louver. Callout 3 points to the side of the louver. Callout 4 points to the bottom of the louver. Callout 5 points to the top of the louver.


- ① TRIANGULAR LOUVER BY G.C.
- ② EFFECTIVE LOUVER AREA. PROVIDE DUCT AND PLENUM BEHIND EFFECTIVE LOUVER AS SHOWN ON DRAWINGS.
- ③ PROVIDE 18 GA. SHEETMETAL 2" INSULATED BLANK OFF PANEL OVER INEFFECTIVE LOUVER AREA. SHEETMETAL TO BE GALVANIZED AND PAINTED BLACK ON EXTERIOR SIDE.
- ④ PROVIDE BLACK BIRDSscreen BEHIND EFFECTIVE LOUVER AREA.

[illegible]

TYPE "A"



TYPE "B"



TYPE "C"

- FIRE DAMPERS SHALL BE UL CLASSIFIED.
- FIRE DAMPERS SHALL BE 1.5 HOUR RATED FOR 2 HOUR RATED WALLS OR LESS; 3 HOUR FIRE RATED FOR 3 HOUR WALLS.
- FIRE DAMPERS SHALL BE DYNAMIC RATED, CURTAIN TYPE, SPRING OPERATED
- DIFFERENTIAL PRESSURE RATING OF 4" MINIMUM, HIGHER WHERE REQUIRED TO MATCH DUCT CONSTRUCTION.
- 2000 FPM MAX. AIRFLOW RATING, EXCEPT 4000 FPM WHERE DESIGN DUCT VELOCITY IS OVER 2000 FPM.
- FIRE CLOSURE FUSIBLE LINK OF 165 DEG. F. EXCEPT WHERE REQUIRED TO BE HIGHER BY APPLICATION.
- GALVANIZED STEEL CONSTRUCTION IN GALVANIZED DUCT, STAINLESS STEEL IN OTHER APPLICATIONS.
- NOMINAL 4" STANDARD FRAME WIDTH.
- INSTALLATION OF FIRE DAMPERS AND ACCESSORIES INCLUDING INSULATION SHALL CONFORM TO NFPA 90A, SMACNA AND MANUFACTURER'S INSTRUCTIONS.
- DETAILS SHOW INSTALLATION OF FIRE DAMPER IN WALL. DAMPER INSTALLATION IN FLOOR SIMILAR. REFER TO PLANS FOR ACCESS LOCATION.

- ① FIRE DAMPER TYPES –
 - TYPE "A" – BLADES STORED IN AIR STREAM.
 - TYPE "B" – BLADES STORED OUT OF AIR STREAM.
 - TYPE "C" – ROUND/OVAL DUCT, BLADES STORED OUT OF AIR STREAM.
- ② ATTACH TO SLEEVE PER SMACNA, MINIMUM 4 CONNECTIONS (2 ON EACH SIDE OF BLADE CHANNEL) PER SIDE, MAX. 6" APART – TACK WELD, #10 SCREWS, 0.25" BOLTS/NUTS OR 3/16" STEEL POP RIVETS.
- ③ SHEETMETAL WALL SLEEVE, SAME MATERIAL AS DUCT. SHEETMETAL GAUGE PER SMACNA. MAINTAIN REQUIRED CLEARANCE TO WALL.
- ④ DUCT/SLEEVE CONNECTION, BREAKAWAY TYPE.
- ⑤ RETAINING ANGLE ALL FOUR SIDES, 1.5"x1.5" LEGS (MIN.). GAUGE PER SMACNA, 1" MINIMUM OVERLAP OF WALL BEYOND OPENING. EXTENDED LEG MAY BE REQUIRED. BOLT, SCREW, OR TACK WELD TO WALL SLEEVE. SPACING OF FASTENERS PER SMACNA.
- ⑥ DUCT ACCESS PANEL OR DOOR – 18"x16" EXCEPT SMALLER WHEN LIMITED BY DUCT SIZE.
- ⑦ CEILING ACCESS PANEL IF CEILING IS NOT ACCESSIBLE.
- ⑧ ROUND DUCT COUPLING.
- ⑨ STAINLESS STEEL CLOSURE SPRING.


NOTE:
AT 2 HR. FIRE WALL WITH DOUBLE WALL CONSTRUCTION, ONLY A SINGLE DAMPER IS REQUIRED PER 2006 NFPA 221
(NOT A HIGH CHALLENGE FIRE WALL) PROVIDE SINGLE SLEEVE CONTINUOUS THRU BOTH WALLS WITH FIRE DAMPER
CENTERED IN SLEEVE FOR GYMNASIUM RETURN AIR, INSTALL SLEEVE DURING CONSTRUCTION OF WALL; TERMINATE
SLEEVE IN MORTAR JOINTS AROUND OPEN AIR BLOCK (GYM SIDE). SLEEVE TO EXTEND THRU CORRIDOR SIDE WALL
AND UTILIZE SINGLE SIDE MOUNTING ANGLE (RUSKIN FAST OR EQUAL). PROVIDE MULTIPLE SECTION DAMPER WITH FRAME
AS REQUIRED FOR OPENING. CENTER TYPE "A" DAMPER(S) IN CORRIDOR SIDE WALL.

3	FIRE DAMPER DETAILS
	N.T.S.

NAUMAN & ZELINSKI LLC.
204 S. Ludlow Street Suite 400 Dayton, Ohio 45402
Phone: (937) 223-3821 ~ Fax: (937) 223-3849

App Architecture
creative focused design

615 Woodside Drive, Englewood, Ohio 45322
T 937.836.8898 F 937.832.3696
www.app-arch.com



Beavercreek Township
Fire Station No. 65
1777 Trebein Road, Beavercreek Township, Ohio 45385

ISSUE:		
NO.	DATE	DESCRIPTION
	04/03/20	FOR CONSTRUCTION

DATE	04/03/20
JOB NO.	3541.00
DRAWN	RAD
CHECKED	RAS
CAD	18102H4.3
COPYRIGHT © 2020 App Architecture, Inc.	
TITLE	
DETAILS	

SHEET NO.

H4.3

Building:

System Tag/Name:

Operating Condition Description:

Units (select from pull-down list)

Beavercreek Fire Station

FRN-1

IP

Inputs for System

Name

Units

System

As

sf

831

Diversity

System

D

100%

100%

17

1,200

Floor area served by system

Population of area served by system

Design primary supply fan airflow rate

OA req'd per unit area for system (Weighted average)

OA req'd per person for system area (Weighted average)

Percent increase in Vbz over minimum required

Ps

P

Vpsd

Ras

Rps

cfm

cfm/sf

cfm/p

17

1,200

0.08

5.0

0%

Inputs for Potentially Critical zones

Zone Name

Zone Tag

Occupancy Category

Floor Area of zone

Design population of zone

Design total supply to zone (primary plus local recirculated)

Induction Terminal Unit, Dual Fan Dual Duct or Transfer Fan?

Frac. of local recirc. air that is representative of system RA

Zone title turns purple italic for critical zone(s)

Select from pull-down list:

P

cfm

Select from pull-down list or leave blank if N/A:

Er

Poten:

Dayro

07

Dayrc

54;

17

80

Inputs for Operating Condition Analyzed

Percent of total design airflow rate at conditioned analyzed

Air distribution type at conditioned analyzed

Zone air distribution effectiveness at conditioned analyzed

Primary air fraction of supply air at conditioned analyzed

Ds

%

Select from pull-down list:

Ez

Ep

100%

Results

System Ventilation Efficiency

Outdoor air intake required for system

Outdoor air per unit floor area

Outdoor air per person served by system (including diversity)

Outdoor air as a % of design primary supply air

Ev

Vot

Vot/As

Vot/Ps

Ypd

cfm

cfm/sf

cfm/p

%

0.94

161

0.19

9.5

13%

FURNACE - FRN-1

161 CFM OA REQUIRED

300 CFM OA PROVIDED

Building:

System Tag/Name:

Operating Condition Description:

Units (select from pull-down list)

Beavercreek Fire Station

FRN-3

IP

Inputs for System

Name

Units

System

As

sf

1,119

Diversity

System

D

100%

100%

11

1,270

Floor area served by system

Population of area served by system

Design primary supply fan airflow rate

OA req'd per unit area for system (Weighted average)

OA req'd per person for system area (Weighted average)

Percent increase in Vbz over minimum required

Ps

P

Vpsd

Ras

Rps

cfm

cfm/sf

cfm/p

11

1,270

0.05

5.5

0%

Inputs for Potentially Critical zones

Zone Name

Zone Tag

Occupancy Category

Floor Area of zone

Design population of zone

Design total supply to zone (primary plus local recirculated)

Induction Terminal Unit, Dual Fan Dual Duct or Transfer Fan?

Frac. of local recirc. air that is representative of system RA

Zone title turns purple italic for critical zone(s)

Select from pull-down list:

P

cfm

Select from pull-down list or leave blank if N/A:

Er

Poten:

Dayro

07

Dayrc

54;

17

80

Inputs for Operating Condition Analyzed

Percent of total design airflow rate at conditioned analyzed

Air distribution type at conditioned analyzed

Zone air distribution effectiveness at conditioned analyzed

Primary air fraction of supply air at conditioned analyzed

Ds

%

Select from pull-down list:

Ez

Ep

100%

Results

System Ventilation Efficiency

Outdoor air intake required for system

Outdoor air per unit floor area

Outdoor air per person served by system (including diversity)

Outdoor air as a % of design primary supply air

Ev

Vot

Vot/As

Vot/Ps

Ypd

cfm

cfm/sf

cfm/p

%

0.81

148

0.13

13.4

12%

FURNACE - FRN-3

148 CFM OA REQUIRED

250 CFM OA PROVIDED

Building:

System Tag/Name:

Operating Condition Description:

Units (select from pull-down list)

Beavercreek Fire Station

FRN-2

IP

Inputs for System

Name

Units

System

As

sf

397

Diversity

System

D

100%

100%

4

800

Floor area served by system

Population of area served by system

Design primary supply fan airflow rate

OA req'd per unit area for system (Weighted average)

OA req'd per person for system area (Weighted average)

Percent increase in Vbz over minimum required

Ps

P

Vpsd

Ras

Rps

cfm

cfm/sf

cfm/p

4

800

0.06

20.0

0%

Inputs for Potentially Critical zones

Zone Name

Zone Tag

Occupancy Category

Floor Area of zone

Design population of zone

Design total supply to zone (primary plus local recirculated)

Induction Terminal Unit, Dual Fan Dual Duct or Transfer Fan?

Frac. of local recirc. air that is representative of system RA

Zone title turns purple italic for critical zone(s)

Select from pull-down list:

P

cfm

Select from pull-down list or leave blank if N/A:

Er

Poten:

Dayro

07

Dayrc

54;

17

80

Inputs for Operating Condition Analyzed

Percent of total design airflow rate at conditioned analyzed

Air distribution type at conditioned analyzed

Zone air distribution effectiveness at conditioned analyzed

Primary air fraction of supply air at conditioned analyzed

Ds

%

Select from pull-down list:

Ez

Ep

100%

Results

System Ventilation Efficiency

Outdoor air intake required for system

Outdoor air per unit floor area

Outdoor air per person served by system (including diversity)

Outdoor air as a % of design primary supply air

Ev

Vot

Vot/As

Vot/Ps

Ypd

cfm

cfm/sf

cfm/p

%

0.97

107

0.27

26.8

13%

FURNACE - FRN-2

107 CFM OA REQUIRED

200 CFM OA PROVIDED

Building:

System Tag/Name:

Operating Condition Description:

Units (select from pull-down list)

Beavercreek Fire Station

FRN-5

IP

Inputs for System

Name

Units

System

As

sf

1,463

Diversity

System

D

100%

100%

2

1,425

Floor area served by system

Population of area served by system

Design primary supply fan airflow rate

OA req'd per unit area for system (Weighted average)

OA req'd per person for system area (Weighted average)

Percent increase in Vbz over minimum required

Ps

P

Vpsd

Ras

Rps

cfm

cfm/sf

cfm/p

2

1,425

0.04

5.0

0%

Inputs for Potentially Critical zones

Zone Name

Zone Tag

Occupancy Category

Floor Area of zone

Design population of zone

Design total supply to zone (primary plus local recirculated)

Induction Terminal Unit, Dual Fan Dual Duct or Transfer Fan?

Frac. of local recirc. air that is representative of system RA

Zone title turns purple italic for critical zone(s)

Select from pull-down list:

P

cfm

Select from pull-down list or leave blank if N/A:

Er

Poten:

Dayro

07

Dayrc

54;

17

80

Inputs for Operating Condition Analyzed

Percent of total design airflow rate at conditioned analyzed

Air distribution type at conditioned analyzed

Zone air distribution effectiveness at conditioned analyzed

Primary air fraction of supply air at conditioned analyzed

Ds

%

Select from pull-down list:

Ez

Ep

100%

Results

System Ventilation Efficiency

Outdoor air intake required for system

Outdoor air per unit floor area

Outdoor air per person served by system (including diversity)

Outdoor air as a % of design primary supply air

Ev

Vot

Vot/As

Vot/Ps

Ypd

cfm

cfm/sf

cfm/p

%

0.77

89

0.06

44.3

6%

FURNACE - FRN-5

89 CFM OA REQUIRED

1425 CFM OA PROVIDED

Building:

System Tag/Name:

Operating Condition Description:

Units (select from pull-down list)

Beavercreek Fire Station

FRN-4

IP

Inputs for System

Name

Units

System

As

sf

1,276

Diversity

System

D

100%

100%

12

1,330

Floor area served by system

Population of area served by system

Design primary supply fan airflow rate

OA req'd per unit area for system (Weighted average)

OA req'd per person for system area (Weighted average)

Percent increase in Vbz over minimum required

Ps

P

Vpsd

Ras

Rps

cfm

cfm/sf

cfm/p

12

1,330

0.05

5.0

0%

Inputs for Potentially Critical zones

Zone Name

Zone Tag

Occupancy Category

Floor Area of zone

Design population of zone

Design total supply to zone (primary plus local recirculated)

Induction Terminal Unit, Dual Fan Dual Duct or Transfer Fan?

Frac. of local recirc. air that is representative of system RA

Zone title turns purple italic for critical zone(s)

Select from pull-down list:

P

cfm

Select from pull-down list or leave blank if N/A:

Er

Poten:

Dayro

07

Dayrc

54;

17

80

Inputs for Operating Condition Analyzed

Percent of total design airflow rate at conditioned analyzed

Air distribution type at conditioned analyzed

Zone air distribution effectiveness at conditioned analyzed

Primary air fraction of supply air at conditioned analyzed

Ds

%

Select from pull-down list:

Ez

Ep

100%

Results

System Ventilation Efficiency

Outdoor air intake required for system

Outdoor air per unit floor area

Outdoor air per person served by system (including diversity)

Outdoor air as a % of design primary supply air

Ev

Vot

Vot/As

Vot/Ps

Ypd

cfm

cfm/sf

cfm/p

%

0.94

125

0.10

10.4

9%

FURNACE - FRN-4

125 CFM OA REQUIRED

350 CFM OA PROVIDED

NAUMAN & ZELINSKI LLC.

204 S. Ludlow Street Suite 400 Dayton, Ohio 45402

Phone: (937) 223-0821 -- Fax: (937) 223-3849

App Architecture
creative focused design

STATE OF OHIO
JEFFREY D. ZELINSKI
63822
REGISTERED PROFESSIONAL ENGINEER

615 Woodside Drive, Englewood, Ohio 45322
T 937.836.8898 F 937.832.3696
www.app-arch.com









Beavercreek Township

Fire Station No. 65

1777 Trebain Road, Beavercreek Township, Ohio 45385






























ISSUE:
NO. DATE DESCRIPTION
04/03/20 FOR CONSTRUCTION

DATE 04/03/20
JOB NO. 3541.00
DRAWN RAD
CHECKED RAS
CAD 18102H0.1
COPYRIGHT © 2020 App Architecture, Inc.
TITLE VENTILATION CALCULATIONS
SHEET NO.
H5.1

ELECTRICAL LEGEND CONT'D	
	DUCT MOUNTED SMOKE DETECTOR (S/SUPPLY, R/RETURN).
	WATER FLOW SWITCH.
	VALVE SUPERVISORY SWITCH.
	DUCT MOUNTED DETECTOR REMOTE TEST STATION AND ALARM INDICATOR LIGHT.
	SMOKE DAMPER.
	FLUSH MOUNTED CEILING SPEAKER.
	FLUSH CEILING MOUNTED FIRE ALARM CALL SYSTEM SPEAKER EXTERIOR DEVICES REQUIRE SINGLE-GANG BOX WITH 3/4" BUSHED CONDUIT STUBBED TO ABOVE ACCESSIBLE INTERIOR CEILING.
	SPEAKER VOLUME CONTROL ROUGH-IN BOX. FLUSH SINGLE-GANG BOX WITH 3/4" BUSHED CONDUIT STUBBED TO ABOVE ACCESSIBLE CEILING IN ROOM SERVED. (46" M.H.).

ELECTRICAL LEGEND CONT'D	
	CEILING MOUNTED LIGHTING CONTROL OCCUPANCY SENSOR, WHERE SUBSCRIPT IS SHOWN, IE: "H-301", INDICATES MULTIPLE SENSORS WIRED TOGETHER TO CONTROL HALLWAY/CORRIDOR LIGHTING.
	EMERGENCY LIGHTING CONTROL RELAY/POWERPACK FOR CONTROL OF LIGHTING ON EMERGENCY CIRCUIT VIA ROOM CEILING MOUNTED OCCUPANCY SENSOR(S) IN CONJUNCTION WITH NORMAL LIGHTS. EQUAL TO "LVS" MODEL EPC-1-D SERIES.
	SINGLE POLE WALL SWITCH (46" M.H.).
	TWO POLE WALL SWITCH (46" M.H.).
	THREE-WAY WALL SWITCH (46" M.H.).
	FOUR-WAY WALL SWITCH (46" M.H.).
	LIGHTING CONTROL WALLBOX TYPE OCCUPANCY SENSOR/SWITCH. ONE-GANG ASSEMBLY (46" M.H.).
	LIGHTING CONTROL WALLBOX TYPE VACANCY SENSOR/SWITCH. ONE-GANG ASSEMBLY (46" M.H.). ("V/D" INDICATES COMBINATION VACANCY SENSOR/DIMMER, EITHER LINE VOLTAGE OR 0-10V AS APPLIES TO FIXTURES CONTROLLED.)
	LIGHTING CONTROL LOW VOLTAGE DIMMER SWITCH. WITH PRESET SLIDE CONTROL AND ON/OFF BUTTON (46" M.H.). LOW VOLTAGE CONTROL COMPATIBLE WITH ROOM OCCUPANCY SENSING CONTROLS AND LED LIGHTING PROVIDED.
	FLUSH FRACTIONAL HORSEPOWER MOTOR STARTER WITH NEON PILOT LIGHT. ONE-GANG ASSEMBLY (46" M.H.).
	HP RATED WALL SWITCH (46" M.H.).
	DISCONNECT SWITCH.
	MOTOR STARTER.
	COMBINATION MOTOR STARTER AND DISCONNECT SWITCH.
	ELECTRIC MOTOR.
	UNIT HEATER.
	FAN COIL UNIT.
	CIRCUIT BREAKER PANEL, FLUSH MOUNTED.
	CIRCUIT BREAKER PANEL, SURFACE MOUNTED.
	POWER PANEL OR SWITCHBOARD, SURFACE MOUNTED.
	LINE VOLTAGE THERMOSTAT.
	WIRELESS ACCESS POINT (CEILING MOUNTED) NO ROUGH-IN BY E.C. REQUIRED.
	TELEPHONE/DATA OUTLET (18" M.H. EXCEPT WHEN SUBSCRIPT LETTER IS SHOWN, "W" INDICATES 46" M.H.). SINGLE GANG OUTLET BOX WITH BLANK COVERPLATE. STUB AN EMPTY 1" BUSHED CONDUIT OUT ABOVE ACCESSIBLE CEILING.
	FIRE ALARM HORN & SIGNAL LIGHT (80" A.F.F.), # WHEN SHOWN INDICATES CANDELA RATING OF STROBE. WHEN A # IS NOT SHOWN, THE STROBE SHALL BE RATED 110 CANDELA.
	FIRE ALARM SIGNALING LIGHT (80" A.F.F.), # WHEN SHOWN INDICATES CANDELA RATING OF STROBE. WHEN A # IS NOT SHOWN, THE STROBE SHALL BE RATED 110 CANDELA.
	FIRE ALARM SENDING STATION (46" M.H.).

INDEX OF DRAWINGS	
<u>SHEET</u>	<u>DRAWING TITLE</u>
E0.1	LEGEND & SCHEDULES
E0.2	SINGLELINE DIAGRAM & SCHEDULES
E0.3	DETAILS
E0.4	DETAILS & SCHEDULES
E0.5	SCHEDULES
E0.6	MSD&C SCHEDULE
E0.7	TECHNOLOGY DETAILS
E1.0	SITE PLAN
E2.1	LEVEL 1 & LEVEL 2 – LIGHTING PLANS
E3.1	LEVEL 1 & LEVEL 2 – POWER PLANS
E4.1	LEVEL 1 & LEVEL 2 – SYSTEMS PLANS

ELECTRICAL LEGEND CONT'D	
	CEILING MOUNTED LIGHTING CONTROL. OCCUPANCY SENSOR. WHERE SUBSCRIPT IS SHOWN, I.E. "14-30", INDICATES MULTIPLE SENSORS WIRED TOGETHER TO CONTROL HALLWAY/CORRIDOR LIGHTING.
	EMERGENCY LIGHTING CONTROL. RELAY/POWERPACK FOR CONTROL OF LIGHTING ON EMERGENCY CIRCUIT VIA ROOM CEILING MOUNTED OCCUPANCY SENSOR(S) IN CONJUNCTION WITH NORMAL LIGHTS. EQUAL TO "LVS" MODEL EPC-1-D SERIES.
	SINGLE POLE WALL SWITCH (46" M.H.).
	TWO POLE WALL SWITCH (46" M.H.).
	THREE-WAY WALL SWITCH (46" M.H.).
	FOUR-WAY WALL SWITCH (46" M.H.).
	LIGHTING CONTROL WALLBOX TYPE OCCUPANCY SENSOR/SWITCH. ONE-GANG ASSEMBLY (46" M.H.).
	LIGHTING CONTROL WALLBOX TYPE VACANCY SENSOR/SWITCH. ONE-GANG ASSEMBLY (46" M.H.). ("D" INDICATES COMBINATION VACANCY SENSOR/DIMMER, EITHER LINE VOLTAGE OR 0-10V AS APPLIES TO FIXTURES CONTROLLED.)
	LIGHTING CONTROL LOW VOLTAGE DIMMER SWITCH WITH PRESET SLIDE CONTROL AND ON/OFF BUTTON (46" M.H.) LOW VOLTAGE CONTROL COMPATIBLE WITH ROOM OCCUPANCY SENSING CONTROLS AND LED LIGHTING PROVIDED.
	FLUSH FRACTIONAL HORSEPOWER MOTOR STARTER WITH NEON PILOT LIGHT. ONE-GANG ASSEMBLY (46" M.H.).
	HP RATED WALL SWITCH (46" M.H.).
	DISCONNECT SWITCH.
	MOTOR STARTER.
	COMBINATION MOTOR STARTER AND DISCONNECT SWITCH.
	ELECTRIC MOTOR.
	UNIT HEATER.
	FAN COIL UNIT.
	CIRCUIT BREAKER PANEL, FLUSH MOUNTED.
	CIRCUIT BREAKER PANEL, SURFACE MOUNTED.
	POWER PANEL OR SWITCHBOARD, SURFACE MOUNTED.
	LINE VOLTAGE THERMOSTAT.
	WIRELESS ACCESS POINT (CEILING MOUNTED) NO ROUGH-IN BY E.C.P. REQUIRED.
	TELEPHONE/DATA OUTLET (18" M.H. EXCEPT WHEN SUBSCRIPT LETTER IS SHOWN, "W" INDICATES 46" M.H.). SINGLE GANG OUTLET BOX WITH BLANK COVERPLATE. STUB AN EMPTY 1" BUSHED CONDUIT OUT ABOVE ACCESSIBLE CEILING.
	FIRE ALARM HORN & SIGNAL LIGHT (80" A.F.F.). # WHEN SHOWN INDICATES CANDELA RATING OF STROBE. WHEN A # IS NOT SHOWN, THE STROBE SHALL BE RATED 110 CANDELA.
	FIRE ALARM SIGNALING LIGHT (80" A.F.F.). # WHEN SHOWN INDICATES CANDELA RATING OF STROBE. WHEN A # IS NOT SHOWN, THE STROBE SHALL BE RATED 110 CANDELA.
	FIRE ALARM SENDING STATION (46" M.H.).
	120 VOLT, COMBINATION SMOKE DETECTOR/CO DETECTOR WITH BATTERY BACKUP, WIRED TO DORM ROOM LIGHTING CIRCUIT. CONNECT ALL SMOKE DETECTORS TOGETHER SUCH THAT ANY DETECTOR IN ALARM CONDITION WILL ACTIVATE ALL DETECTOR ALARMS. (3 WIRE INTERCONNECTION). WIRE TO BUILDING FIRE ALARM SYSTEM (VIA AUXILIARY CONTACTS TO SIGNAL BUILDING FIRE ALARM SYSTEM UPON ALARM CONDITION. EQUAL TO GENTEX MODEL # GN-503FF.
	FIRE ALARM SYSTEM CEILING MOUNTED SMOKE DETECTOR.
	120 VOLT, RED FLASHING STROBE SIGNALING LIGHT, WIRED TO RELAY IN I.T. ROOM TO BE CONTROLLED FROM "MACH ALERT" FIRE SIGNALING SYSTEM OUTPUT CONTACT, EQUAL TO TORK #TA1310R15 (DOUBLE FLASH SUPER STROBE WITH RED LEXAN LENS, 0.2 AMPS). 7.5" DIA. X 5 1/4" H. MOUNT INVERTED TO SOFFIT WHERE SHOWN ON BUILDING EXTERIOR. MOUNT INVERTED TO BOTTOM OF CEILING TRUSS IN APPARATUS BAY.

ELECTRICAL LEGEND

	ELECTRICAL CONNECTION REQUIRED.
	EXIT LIGHTING FIXTURE. ARROWS AS INDICATED.
	LIGHTING FIXTURE: CAPITAL LETTER DENOTES FIXTURE TYPE. LOWER CASE LETTER DENOTES SWITCHING ARRANGEMENT.
	LIGHTING FIXTURE ON NIGHT LIGHT OR EMERGENCY CIRCUIT.
	WIRE RUN IN SURFACE WIREWAY.
	WIRE & CONDUIT FOR NIGHT LIGHT CIRCUITRY.
	WIRE & CONDUIT FOR EMERGENCY CIRCUITRY.
	EXISTING WIRE & CONDUIT.
	EACH ARROWHEAD REPRESENTS ONE COMPLETE CIRCUIT. CAPITAL LETTER DENOTES PANEL, NUMBER DENOTES CIRCUIT.
	WIRE & CONDUIT IN WALL OR ABOVE CEILING.
	WIRE & CONDUIT IN OR BELOW SLAB OR BELOW GRADE.
	JUNCTION BOX.
	DASHED SYMBOL INDICATES THAT PARTICULAR OUTLET OR DEVICE TO BE REMOVED AND CIRCUITRY MADE CONTINUOUS WHERE REQUIRED.
	EXISTING OUTLET OR DEVICE TO REMAIN, MAINTAIN EXISTING CIRCUITRY.
	20A-125V SINGLE RECEPTACLE, NEMA 5-20R (18" M.H.).
	20A-125V DUPLEX RECEPTACLE, NEMA 5-20R (18" M.H.).
	SPECIAL PURPOSE RECEPTACLE. REFER TO NOTE ON PLAN.
	20A-125V DOUBLE DUPLEX RECEPTACLE, NEMA 5-20R, (18" M.H.) TWO-GANG ASSEMBLY.
	20A-125V DUPLEX RECEPTACLE, NEMA 5-20R, (46" M.H.). SUBSCRIPT "GF" INDICATES GFCI TYPE RECEPTACLE. SUBSCRIPT "U" INDICATES INTEGRAL USB CHARGING PORTS. SUBSCRIPT "GF/NL" INDICATES GFCI RECEPTACLE WITH INTEGRAL LED NIGHT LIGHT.
	20A-125V DUPLEX RECEPTACLE WITH TWO INTEGRAL USB CHARGING PORTS (18" M.H.).
	20A-125V DUPLEX RECEPTACLE, NEMA 5-20R, WITH GROUND FAULT CIRCUIT INTERRUPTER (18" M.H.).
	20A-125V WEATHERPROOF DUPLEX RECEPTACLE, NEMA 5-20R, WITH GROUND FAULT CIRCUIT INTERRUPTER (18" M.H.), WITH HUBBELL #WP26M CAST ALUMINUM "WHILE-IN-USE" COVER.
	20A-125V DUPLEX RECEPTACLE, NEMA 5-20R, IN HUBBELL BA-2436 FLUSH FLOOR BOX WITH SA-3825 COVERPLATE. PROVIDE CARPET FLANGE WHERE REQUIRED.
	20A-125V/250V-1PH-4W SINGLE RECEPTACLE, NEMA 14-20R (18" M.H.).
	30A-125V/250V-1PH-4W SINGLE RECEPTACLE, NEMA 14-30R (18" M.H.).
	50A-125V/250V-1PH-3W SINGLE RECEPTACLE, NEMA 14-50R (6" M.H.).
	WALL MONITOR OUTLET ASSEMBLY CONSISTING OF DUPLEX RECEPTACLE AND DATA/HDMI/AV CONNECTION IN RECESSED BOX WITH 1" C. TO ABOVE CEILING. MOUNTING HEIGHT AS NOTED, REFER TO ARCHITECTURAL ELEVATIONS. PROVIDE RG6 COAX WIRING FROM EACH T.V. OUTLET TO I.T. ROOM FOR FUTURE TERMINATION BY CATV SYSTEM PROVIDER. PROVIDE "f" TYPE CONNECTORS ON EACH END WITH 25' COIL IN I.T. ROOM.
	INTERCOM/DOORBELL SYSTEM ROUGH-IN BOX. FLUSH SINGLE-GANG BOX WITH 3/4" BUSHED CONDUIT STUBBED TO ABOVE INTERIOR ACCESSIBLE CORRIDOR CEILING. (46" M.H.).
	WIRELESS ACCESS PORT (ROUTER) ROUGH-IN BOX, FLUSH CEILING MOUNTED IN APPARATUS BAY, FLUSH WALL MOUNTED WHERE SHOWN ON BUILDING EXTERIOR (84" M.H.). SINGLE-GANG WITH 3/4" BUSHED CONDUIT HOMERUN TO SERVER ROOM (FOR APPARATUS BAY), STUBBED TO ABOVE ACCESSIBLE INTERIOR CEILING FOR EXTERIOR DEVICES.
	ACCESS CONTROL/CARD READER SYSTEM ROUGH-INS REFER TO DETAIL SHEET E.07
	SECURITY CAMERA SYSTEM ROUGH-IN BOX, CONDUIT AND DATA WIRING BACK TO I.T. ROOM (SYMBOL WITH "C" DESIGNATION), REFER TO DETAILS ON SHEET E.07.







GENERAL NOTES

- A. ALL WORK SHALL BE IN ACCORDANCE WITH THE 2017 OHIO BUILDING CODE AND 2017 NEC, INCLUDING REFERENCED CODES AND STANDARDS, ALL LOCAL AND STATE CODES AND MEET APPROVAL OF AUTHORITIES HAVING JURISDICTION.
- B. BIDDERS SHALL INSPECT PROJECT SITE EXISTING CONDITIONS DURING BIDDING.
- C. INCLUDE PAYMENT OF ALL PERMIT AND INSPECTION FEES AND OBTAIN AN ELECTRICAL PERMIT AND SECURE INSPECTION AND APPROVAL OF THE CODE OFFICIAL.
- D. SUBMIT AN ELECTRONIC COPY OF SUBMITTAL DATA AND DESCRIPTIVE LITERATURE IN .PDF FORMAT FOR ALL FIXTURES AND EQUIPMENT.
- E. WORKMANSHIP SHALL BE OF THE HIGHEST QUALITY AND REPRESENT THE BEST PRACTICES OF THE INDUSTRY.
- F. COORDINATE INSTALLATION WITH OTHER TRADES; PROVIDE OFFSETS AS REQUIRED.
- G. INSTALL ALL MATERIALS AND EQUIPMENT IN ACCORDANCE WITH MANUFACTURERS REQUIREMENTS.
- H. COORDINATE EACH ROUGH-IN INSTALLATION REQUIREMENTS AND LOCATIONS WITH OTHER TRADES, ACTUAL EQUIPMENT OR CABINERY PROVIDED AND FIELD CONDITIONS BEFORE PERFORMING WORK.
- I. REFER TO ARCHITECTURAL DRAWING ELEVATIONS FOR MOUNTING LOCATION INFORMATION, ARRANGEMENT AND HEIGHT FOR ALL DEVICES AT FURNISHINGS, CASEWORK, ETC.
- J. REFER TO ARCHITECTURAL REFLECTED CEILING PLANS FOR EXACT LOCATION OF ALL LIGHTING FIXTURES. WHERE DISCREPANCIES MAY OCCUR BETWEEN THE ELECTRICAL PLANS AND THE ARCHITECTURAL CEILING PLANS ON QUANTITY OF FIXTURES, THE ELECTRICAL PLANS SHALL TAKE PRECEDENCE. COORDINATE FIXTURE LOCATIONS WITH OTHER TRADES TO AVOID CONFLICTS WITH PIPING AND DUCTWORK.
- K. ALL EQUIPMENT AND MATERIAL REQUIRED FOR COMPLETE AND FUNCTIONAL ELECTRICAL SYSTEMS SHALL BE INCLUDED IN THE CONTRACT.

GENERAL NOTES - FIRESTOPPING

1. THIS CONTRACTOR SHALL FIRESTOP ALL PENETRATIONS OF NEW AND EXISTING RATED WALLS AND PARTITIONS UTILIZING APPROPRIATE APPROVED UL LISTED S.T.I. FIRESTOPPING SYSTEM. REFER TO SPECIFICATIONS.
2. REFER TO ARCHITECTURAL DRAWINGS FOR LOCATIONS OF ALL FIRE AND SMOKE RATED WALLS AND PARTITIONS.
3. THIS CONTRACTOR SHALL FIRESTOP ALL RACEWAY AND MIREWAY PENETRATIONS OF FLOORS UTILIZING APPROPRIATE APPROVED UL LISTED S.T.I. FIRESTOPPING SYSTEM. REFER TO SPECIFICATIONS.

GENERAL LEGEND

EC	ELECTRICAL CONTRACT.
FC	FIRE PROTECTION CONTRACTOR.
GC	GENERAL CONTRACTOR.
HC	HVAC CONTRACTOR.
PC	PLUMBING CONTRACTOR.
TC	TEMPERATURE CONTROLS CONTRACTOR.
NIC	NOT IN CONTRACT.
AFF	ABOVE FINISHED FLOOR — TO BOTTOM OF ITEM UNLESS INDICATED OTHERWISE IN DRAWING.
(E)	EXISTING.
ES	EQUIPMENT SUPPLIER.
EM	EMERGENCY.
MH	MOUNTING HEIGHT.
S	SURFACE MOUNTED.
WP	WEATHER PROOF.
	NOTE SYMBOL — APPLIES ONLY TO SHEET ON WHICH IS SHOWN.
	DETAIL NOTE SYMBOL — APPLIES ONLY TO DETAIL ON WHICH IS SHOWN.
	EQUIPMENT REFERENCE SYMBOL. ELECTRICAL CONNECTION REQUIRED.
	ROOM NUMBER.
	DETAIL SYMBOL DETAIL "B" SHOWN ON SHEET H2.
	SECTION SYMBOL SECTION "A" DESIGNATION, SHOWN ON SHEET H1.
----	ITEM TO BE REMOVED.
_____	EXISTING ITEM TO REMAIN.
=====	NEW ITEM.

SEISMIC REQUIREMENTS

THIS PROJECT HAS SEISMIC REQUIREMENTS.
REFER TO DRAWING H0.1.

NAUMAN & ZELINSKI LLC.
204 S. Ludlow Street Suite 400 Dayton, Ohio 45402
Phone: (937) 223-3821 – Fax: (937) 223-3849

App Architecture
creative focused design

645 Woodside Drive, Englewood, Ohio 45322
T 937.836.8898 F 937.832.3696
www.app-arch.com



Beavercreek Township

Fire Station No. 65

1777 Trebein Road, Beavercreek Township, Ohio 45385

ISSUE:		
NO.	DATE	DESCRIPTION
	04/03/20	FOR CONSTRUCTION

DATE	04/03/20
JOB NO.	3541.00
DRAWN	DAC
CHECKED	TCR
CAD	16544E.1
COPYRIGHT © 2020 App Architecture, Inc.	
TITLE	

SHEET NO.

EO.1

--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

App Architecturecreative focused design

645 Woodside Drive, Englewood, Ohio 4

Note: The Electrical Equipment Supplier/Manufacturer shall perform a selective coordination study for the Emergency/Life-Safety Distribution System to confirm that all supply side overcurrent devices are coordinated as required by NEC 700.32.
The E.C. shall be responsible to modify the Life-Safety Distribution and associated conductor sizing to meet the requirements of the Selective Coordination Study.

STANDBY DISTRIBUTION PANEL "SDP" (22k AIC RATING)											
SPEC. REFERENCE NO.:			CONNECTED LOAD:				101 KVA				
MAIN BUSSING:			400 AMPS		DEMAND LOAD:			76 KVA (317 AMPS)			
FEEDER SIZE:			SEE "MDP" SCHEDULE		VOLTAGE:			120/240V-1PH-3W			
SWITCH OR UNIT NO.	NAMEPLATE	APPROX. CONNECTED KVA LOAD	OVERCURRENT PROTECTION				FEEDER				
			FRAME SIZE	POLES	TRIP RATING	SEE NOTE	NUMBER OF CONDUCTORS	WIRE SIZE	GROUND SIZE	CONDUIT SIZE	
	PANEL "SP1"	28 KVA	200	2	200		3	250 (AL)	6 (CU)	2.5	
	PANEL "SP2"	20 KVA	200	2	200		3	250 (AL)	6 (CU)	2.5	
	PANEL "SP3"	53 KVA	200	2	200		3	250 (AL)	6 (CU)	2.5	
	SPARE		100	2	100						
	SPD		60	2	60						

NOTES:
1.

MAIN DISTRIBUTION PANEL "MDP" (22k AIC RATING)											
SPEC. REFERENCE NO.:			CONNECTED LOAD:				152 KVA				
MAIN BUSSING:			600 AMPS			DEMAND LOAD:			121 KVA (504 AMPS)		
FEEDER SIZE:			3 SETS OF 4-#250 KCMIL (AL.)			VOLTAGE:			120/240V-1PH-3W		
SWITCH OR UNIT NO.	NAMEPLATE	APPROX. CONNECTED KVA LOAD	OVERCURRENT PROTECTION				FEEDER				
			FRAME SIZE	POLES	TRIP RATING	SEE NOTE	NUMBER OF CONDUCTORS	WIRE SIZE	GROUND SIZE	CONDUIT SIZE	
	ATS "SB"	101 KVA	400	2	400		2 SETS OF 3	250 (AL)	3 (CU)	2.5	
	ATS "LS"	16 KVA	100	2	100		3	2 (CU)	8 (CU)	1.25	
	PANEL "AC"	36 KVA	200	2	200		3	250 (AL)	3 (CU)	2.5	
	SPD		60	2	60						

NOTES:
1.

PANEL "SP1" (10k AIC Rating)											
MOUNTING: SURFACE (ELEC ROOM)											
CONN. LOAD: 28 KVA			DEMAND LOAD: 20 KVA (83 AMPS)								
MAINS: 200A M.L.O.			VOLTAGE: 120/240V-1PH-3W								
REMARKS	DEMAND KVA	CONNECTED KVA	BKLR	CKT. NO.	BKLR	CONNECTED KVA	DEMAND KVA	REMARKS			
REFRIG		1.0-R	20/1	1	2	50/2	7.0-H	RANGE #			
REFRIG		1.0-R	20/1	3	4	-					
REFRIG		1.0-R	20/1	5	6	20/1	0.4-R	COUNTER REC			
ISLAND REC		0.4-R	20/1	7	8	20/1	0.8-R	PENINSULA			
COUNTER REC		0.6-R	20/1	9	10	20/1	0.5-M	EF1			
COUNTER REC		0.6-R	20/1	11	12	20/1	1.0-R	CONFERENCE			
COFFEE MAKER		0.5-R	20/1	13	14	20/1	1.0-R	CONFERENCE			
DISPOSER		1.0-M	20/1	15	16	20/1	1.0-R	CORRIDOR			
MICROWAVE		1.2-R	20/1	17	18	20/1	0.5-C	ACCESS CONTROL			
DISHWASHER		1.0-R	20/1	19	20	20/1	0.5-R	R/O SYSTEM			
WORKOUT		1.0-R	20/1	21	22	20/1	0.4-R	TOOL STOR			
WORKOUT		1.0-R	20/1	23	24	20/1	1.0-R	BATT STAT.			
WORKOUT		1.0-R	20/1	25	26	20/1	0.5-R	REPORT			
WORKOUT		1.0-R	20/1	27	28	20/1	0.5-R	REPORT			
SPARE			20/1	29	30	20/1	0.5-R	REPORT			
SPARE			20/1	31	32	20/1		SPARE			
SPARE			20/1	33	34	20/1		SPARE			
SPARE			20/1	35	36	20/1		SPARE			
SPARE			20/1	37	38	20/1		SPARE			
SPARE			20/1	39	40	20/1		SPARE			
SPARE			20/1	41	42	20/1		SPARE			


PROVIDE GFCI TYPE CIRCUIT BREAKER FOR RANGE CIRCUIT

PANEL "SP2" (10k AIC Rating)											
MOUNTING: SURFACE (ELEC ROOM)											
CONN. LOAD: 20 KVA			DEMAND LOAD: 16 KVA (67 AMPS)								
MAINS: 200A M.L.O.			VOLTAGE: 120/240V-1PH-3W								
REMARKS	DEMAND KVA	CONNECTED KVA	BKLR	CKT. NO.	BKLR	CONNECTED KVA	DEMAND KVA	REMARKS			
EUH-1		1.5-H	20/1	1	2	20/1	0.8-R	DORM *			
EUH-3		1.5-H	20/1	3	4	20/1	0.8-R	DORM *			
EUH-2		1.5-H	20/1	5	6	20/1	0.8-R	DORM *			
ELEC. RM.		0.4-R	20/1	7	8	20/1	0.8-R	DORM *			
GEN BATT CHRG		1.0-C	20/1	9	10	20/1	0.8-R	DORM *			
GEN BLOCK HTR		1.5-H	20/1	11	12	20/1	0.8-R	DORM *			
EMS		0.8-R	20/1	13	14	20/1	1.0-R	TR's			
EMS		0.5-R	20/1	15	16	20/1	1.4-R	OFFICE			
EMS		5.0-H/M	50/2	17	18	20/1	0.4-R	UTILITY			
DRYER				19	20	20/1	1.0-M	WASHER			
EMS WASH		1.2-M	20/1	21	22	20/1	0.8-R	TOG DEHUM			
TOG DRYER			60/2	23	24	20/1	0.8-R	TOG			
				25	26	20/1	0.8-R	TOG			
SPARE			20/1	27	28	30/2	5.0-M/H	DRYER #			
SPARE			20/1	29	30	-					
SPARE			20/1	31	32	20/1		SPARE			
SPARE			20/1	33	34	20/1		SPARE			
SPARE			20/1	35	36	20/1		SPARE			
SPARE			20/1	37	38	20/1		SPARE			
SPARE			20/1	39	40	20/1		SPARE			
SPARE			20/1	41	42	20/1		SPARE			


* PROVIDE AFCI TYPE CIRCUIT BREAKER FOR DORM ROOM CIRCUIT
PROVIDE GFCI TYPE CIRCUIT BREAKER FOR DRYER CIRCUIT

PANEL "SP3" (10k AIC Rating)											
MOUNTING: FLUSH (TRAINING RM)											
CONN. LOAD: 53 KVA			DEMAND LOAD: 40 KVA (167 AMPS)								
MAINS: 200A M.L.O.			VOLTAGE: 120/240V-1PH-3W								
REMARKS	DEMAND KVA	CONNECTED KVA	BKLR	CKT. NO.	BKLR	CONNECTED KVA	DEMAND KVA	REMARKS			
APP LTS		0.5-L	20/1	1	2	20/1	1.0-M	OHD1			
CF1		1.0-M	20/1	3	4	20/1	1.0-M	OHD2			
CF1		1.0-M	20/1	5	6	20/1	1.0-M	OHD3a			
WTR RM		1.6-R	20/1	7	8	20/1	1.0-M	OHD3b			
SPARE			20/1	9	10	20/1	0.6-M	RH1			
SPARE			20/1	11	12	20/1	0.6-M	RH2			
SPARE			20/1	13	14	20/1	0.6-M	RH3			
SPARE			40/2	15	16	20/1	0.6-M	RH4			
				17	18	20/1	0.7-M	UH-1			
EXT. REC		1.0-R	20/1	19	20	20/2	2.0-M	EF-2			
EXT. LTG.		0.2-L	20/1	21	22	-					
CORD REEL		1.0-R	20/1	23	24	15/1	1.3-M	F-1			
CORD REEL		1.0-R	20/1	25	26	15/1	1.3-M	F-2			
CORD REEL		1.0-R	20/1	27	28	15/1	1.3-M	F-3			
CORD REEL		1.0-R	20/1	29	30	20/1	1.8-M	F-4			
AIR COMP.		6.0-M	50/2	31	32	15/1	1.3-M	F-5			
				33	34	20/1	0.5-M	WTR HTR			
EUH-4		3.0-H	20/2	35	36	20/2	4.0-M	ACU-1			
				37	38	-					
SANITARY PUMP		9.0-M	60/2	39	40	60/2	9.0-M	CU4			
				41	42	-					
SPARE			20/1	43	44	20/1		SPARE			
SPARE			20/1	45	46	20/1		SPARE			
SPARE			20/1	47	48	20/1		SPARE			
SPARE			20/1	49	50	20/1		SPARE			

PANEL "LS1" (10k AIC Rating)					MOUNTING:		SURFACE	
CONN. LOAD:		16 KVA		DEMAND LOAD:		16 KVA (67 AMPS)		
MAINS:		100A M.B.		VOLTAGE:		120/240V-1PH-3W		
REMARKS	DEMAND KVA	CONNECTED KVA	BKLR	CKT. NO.	BKLR	CONNECTED KVA	DEMAND KVA	REMARKS
INTERIOR LTG		1.0-L	20/1	1	2	20/1	1.0-L	APP BAY LTG.
EXTERIOR LTG		0.5-L	20/1	3	4	30/2	2.5-R	SERVER RM.
EXTERIOR LTG		0.5-L	20/1	5	6	-		
F.A. PANEL		0.5-C	20/1	7	8	30/2	2.5-R	SERVER RM.
FM 200 (I.T.)		0.5-C	20/1	9	10	-		
ACCESS CNTRL.		1.0-R	20/1	11	12	30/2	2.5-R	SERVER RM.
SPARE			20/1	13	14	-		
SPARE			20/1	15	16	20/1	1.0-R	SERVER RM.
SPARE			20/1	17	18	20/1	1.0-R	SERVER RM.
SPARE			20/1	19	20	20/1	1.0-R	SERVER RM.
SPARE			20/1	21	22	20/1	1.0-R	SERVER RM.
SPARE			20/1	23	24	20/1	1.0-R	ACCESS CNTRL.
SPARE			20/1	25	26	30/3		SPD
SPARE			20/1	27	28	-		
SPARE			20/1	29	30	-		




**APPARATUS BAY
FAN CONTROL DETAIL**
SCALE: N.T.S.





APPARATUS BAY CONTROL PANEL DETAIL
SCALE: N.T.S.

- # DETAIL NOTES**
- FLUSH MOUNTED ENCLOSURE WITH STAINLESS STEEL HINGED COVER FOR MOUNTING OF APPARATUS BAY LIGHT SWITCHES (2), CIRCULATION FAN CONTROLS (2), APPARATUS BAY EXHAUST SYSTEM CONTROLS (WITH OVERRIDE BUTTON), CO ALARM INDICATION LIGHT, KITCHEN EM SHUTOFF BUTTON, OVERRIDE CONTROL BUTTONS FOR APPARATUS BAY RADIANT HEAT SYSTEM.
 - TOGGLE TYPE LIGHTING CONTROL SWITCH FOR APPARATUS BAY.
 - MAINTAINED CONTACT N.C., JUMBO MUSHROOM HEAD PUSH BUTTON ALLEN BRADLEY 800H OR APPROVED EQUAL.
 - APPARATUS BAY CIRCULATION FAN CONTROLLER (ON/OFF/REVERSE/SPEED), EQUAL TO GLOBAL INDUSTRIAL, CANARM #WR3653108 VARIABLE SPEED FAN CONTROL, PERMITS CONTROL OF UP TO 4 CANARM #WR3653104 FANS SPECIFIED. IF DIFFERENT FAN IS PROVIDED, E.C. SHALL PROVIDE COMPATIBLE FAN SPEED CONTROLLER MATCHED TO FANS PROVIDED.
 - EXHAUST FAN OVERRIDE SWITCH. REFER TO APPARATUS BAY EXHAUST FAN CONTROL DETAIL, THIS SHEET FOR ADDITIONAL REQUIREMENTS. LOCATE COMPONENTS WITHIN ENCLOSURE. COORDINATE CONTROL REQUIREMENTS WITH H.C.
 - RADIANT HEATER OVERRIDE SWITCH. (RH-1 & RH-2)
 - RADIANT HEATER OVERRIDE SWITCH. (RH-3 & RH-4)
 - UNIT HEATER OVERRIDE SWITCH. WIRE IN PARALLEL WITH THERMOSTAT TO BYPASS THERMOSTAT.
 - OVERRIDE SWITCHES FURNISHED BY H.C., INSTALLED AND WIRED BY E.C. COORDINATE WIRING REQUIREMENTS WITH H.C. AND EQUIPMENT VENDOR.
 - APPARATUS BAY CALL SPEAKERS VOLUME CONTROL.



TYPICAL DORM ROOM DIAGRAM
SCALE: N.T.S.



CONTROL DIAGRAM KITCHEN POWER
SCALE: N.T.S.


- # DETAIL NOTES**
- LIGHTING CONTROL RELAY PANEL "RP1". REFER TO SHEET E3.1 FOR LOCATION (ON MEZZANINE), REFER TO "RELAY LOAD AND CONTROL REQUIREMENTS SCHEDULE" THIS SHEET, FOR ADDITIONAL REQUIREMENTS.
 - MOMENTARY CONTACT N.O., JUMBO MUSHROOM HEAD PUSH BUTTON ALLEN BRADLEY 800H-DR6JA OR APPROVED EQUAL. TO BE MOUNTED IN APPARATUS BAY CONTROL PANEL. SEE SHEET E3.1 FOR LOCATION, THIS SHEET FOR APPARATUS BAY PANEL DETAIL.
 - PROVIDE 60A/3P ELECTRICALLY HELD LIGHTING CONTACTOR (LOCATED ON WALL NEXT TO RELAY PANEL) FOR RANGE RECEPTACLE CIRCUIT. CONTACTOR SHALL HAVE 120V CONTROL RELAY. WIRE SUCH THAT RELAY IS NORMALLY DE-ENERGIZED AND CONTACTS ARE CLOSED (POWER AVAILABLE TO RANGE WHEN RELAY IN RELAY PANEL IS OFF). WHEN AN EMERGENCY STOP BUTTON IS DEPRESSED, RELAY IN RELAY PANEL SHALL ENERGIZE LIGHTING CONTRACTOR RELAY AND OPEN CONTACTS.

SUSPENDED OVERHEAD CIRCULATION FANS (FURNISHED/INSTALLED BY E.C. REFER TO SPEC SECTION 26 ____)


[illegible]

NOTES:


1. 56" BLADE DIAMETER (PENDANT SUSPENDED) CIRCULATION FAN WITH REMOTE WALL CONTROLLER. WALL CONTROLLER LOCATED IN APPARATUS BAY CONTROL PANEL.
2. 36" DIAMETER (CEILING-HUGGER) STYLE CIRCULATION FAN, WHITE FINISH.




#	UNDERGROUND DUCTS
	N.T.S.




#	UNDERGROUND DUCTS
	N.T.S.



#	UNDERGROUND DUCT
	N.T.S.




BL1	BOLLARD BASE DETAIL
	N.T.S.



PL1	TYPICAL POLE BASE DETAIL
	N.T.S.

NAUMAN & ZELINSKI LLC.
204 S. Ludlow Street Suite 400 Dayton, Ohio 45402
Phone: (937) 223-3821 ~ Fax: (937) 223-3849



Beavercreek Township

Fire Station No. 65

1777 Trebein Road, Beavercreek Township, Ohio 45385

ISSUE:		
NO.	DATE	DESCRIPTION
	04/03/20	FOR CONSTRUCTION

DATE	04/03/20
JOB NO.	3541.00
DRAWN	DAC
CHECKED	TCR
CAD	16544E0.5

COPYRIGHT © 2020 App Architecture, Inc.

TITLE

**SCHEDULES
& DETAILS**

SHEET NO.

E0.5

MOTORS, STARTERS, DISCONNECTS & CONTROLS

MOTOR										STARTER								DISCONNECT MEANS								CONTROL				FEEDER																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																											
MOTOR NUMBER	CIRCUIT NUMBER	NAMEPLATE	CHARACTERISTICS						NEMA SIZE	TYPE					LOCATION					TYPE					LOCATION					FURNISHED BY	INTERLOCK W/ DAMPER, BY E.C.	MANUAL AT STARTER	INTEGRAL W/ EQUIP. BY H.C.	SEE NOTE	NO. OF CONDUCTORS	WIRE SIZE	GRD. SIZE	CONDUIT SIZE	SEE NOTE																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																		
			HP, KVA OR FLA (MCA MIN, CIRCUIT AMPS MOC MAX OVERCURRENT PROT)	120V-1PH	208V-3PH	240V-1PH	480V-1PH	480V-3PH		LOCATION	MANUAL	MAGNETIC	BUILT-IN MOTOR OIL	VFD	VFD w/BYPASS	NEAR MOTOR	MOTOR CONT. CNTR.	EQUIP. CONT. PANEL	ROOM NUMBER	SEE NOTE	FURNISHED BY	DISC. SWITCH	MANUAL STARTER	RECEPTACLE	BREAKER	FUSIBLE	NEAR MOTOR	MOTOR CONT. CNTR.	EQUIP. CONT. PANEL											PANELBOARD	SEE NOTE																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																

NOTES:
1. E.C. TO PROVIDE MANUAL SWITCH IN KITCHEN ADJACENT TO RANGE, WIRE IN PARALLEL WITH HOOD AUTOMATIC HEAT SENSOR CONTROLS (FURNISHED WITH HOOD).
2. FC-1 (INDOOR UNIT) POWERED FROM ACU-1 (OUTDOOR UNIT). COORDINATE WIRING REQUIREMENTS WITH H.C. PER MANUFACTURER'S REQUIREMENTS (PROVIDE LOCAL SERVICE DISCONNECT).
3. COORDINATE CONNECTION REQUIREMENTS FOR HOT WATER CIRCULATION & RECIRC PUMPS WITH P.C., INLINE PUMP MOUNTED ADJACENT TO WATER HEATER & STORAGE TANK. PROVIDE TOGGLE TYPE SERVICE DISCONNECT ON WALL ADJACENT TO EACH PUMP (IF NOT CORD/PLUG CONNECTED. CONNECT PUMPS TO SAME RECEPTACLE CIRCUIT SERVING WATER HEATER.



ISSUE:		
NO.	DATE	DESCRIPTION
	04/03/20	FOR CONSTRUCTION

DATE	04/03/20
JOB NO.	3541.00
DRAWN	DAC
CHECKED	TCR
CAD	16544E0.6

COPYRIGHT © 2020 App Architecture, Inc.


TITLE
MSDC&
SCHEDULE

SHEET NO.


E0.6

GENERAL NOTES:


- A QUANTITY OF NETWORK NODES IS DEPENDANT UPON THE BIDDERS CONFIGURATION OF SYSTEM LAYOUT.
- B THE EXISTING NETWORK CONTROLLER IS LOCATED ON THE TELECOMMUNICATIONS BACKBOARD IN THE I.T. ROOM.
- C NETWORK NODES SHALL BE MOUNTED IN SECURE CLOSETS OR AS INDICATED ON FLOOR PLAN.
- D ALL DOOR HARDWARE SHALL BE PROVIDED AND INSTALLED BY THE DIVISION 08 SUPPLIER.
- E ALL TERMINATIONS TO THE DOOR HARDWARE PROVIDED BY DIVISION 08 SHALL BE THE RESPONSIBILITY OF THE SECURITY CONTRACTOR.
- F THIS CONTRACTOR SHALL COORDINATE THE INSTALLATION OF ALL CABLES, CABLE PATHWAYS, DEVICE LOCATIONS, AND ALL OTHER TERMINATIONS WITH THE ELECTRICAL CONTRACTOR, DIVISION 08 SUPPLIER, CM, AND ARCHITECT AS REQUIRED PRIOR TO INSTALLATION.




A ACCESS CONTROL SYSTEM DIAGRAM
N.T.S.




1 SEMI-FLUSH CEILING MOUNTED



2 SURFACE CEILING MOUNTED




3 PENDANT MOUNTED



4 SEMI-FLUSH WALL MOUNTED


E CAMERA MOUNTING SCHEMATICS
N.T.S.




C CCTV SYSTEM SCHEMATIC
N.T.S.

CODED NOTES:

- 1 CABLING TO ACCESS CONTROL SYSTEM CONTROLLER (BY DIVISION 26).
- 2 CABLING TO INTRUSION DETECTION SYSTEM PANEL (BY DIVISION 26).
- 3 J-HOOK SPACED A MAXIMUM OF 48" (TYPICAL) (BY DIVISION 26).
- 4 ACCESS CONTROL SYSTEM CARD READER (BY DIVISION 26).
- 5 3/4" CONDUIT (BY DIVISION 26) FOR ACCESS TO CARD READER.
- 6 3/4" CONDUIT FOR ACCESS TO DOOR STRIKE (BY DIVISION 26).
- 7 OMITTED.
- 8 ELECTRIC LOCK POWER SUPPLY PROVIDED BY OTHERS (QUANTITY OF 4). 120V POWER BY DIVISION 26. COORDINATE TERMINATION OF LOCK RELEASE CABLING WITH THE DOOR HARDWARE INSTALLER.
- 9 FINISHED CEILING.
- 10 4-SQUARE JUNCTION BOX BY E.C.




D SECURITY ACCESS CONTROL DETAILS
N.T.S.




F TYPICAL RACK ELEVATION
N.T.S.

TELECOMMUNICATIONS RACK EQUIPMENT SCHEDULE	
EQUIPMENT NUMBER	DESCRIPTION
1	FIBER OPTIC ENCLOSURE (BY OTHERS)
2	CAT 6 PATCH PANEL (BY OTHERS)
3	48 PORT CAT 6 PATCH PANEL (BY E.C. AS REQUIRED FOR DATA AND CCTV CABLING INSTALLED)
4	48 PORT SWITCH (BY OTHERS)
5	2U HORIZONTAL WIRE MANAGEMENT (BY OTHERS)
6	UNINTERRUPTIBLE POWER SUPPLY (BY OTHERS)
8	VERTICAL WIRE MANAGEMENT FRONT AND BACK SIDE
9	EQUIPMENT RACK (BY OTHERS)
10	VERTICAL POWER STRIP (BY OTHERS)
13	DVR (BY CCTV SYSTEM VENDOR)
14	WIRELESS LAN CONTROLLER (BY OTHERS)
15	48 PORT SWITCH PoE (FOR CCTV, BY E.C.)
24	EQUIPMENT RACK/CABINET GROUNDING BUSBAR (MOUNTED IN REAR)




G LADDER RACK INSTALLATION DETAIL
N.T.S.



H COMMUNICATIONS OUTLET FACEPLATE DETAILS
N.T.S.

NAUMAN & ZELINSKI LLC.
204 S. Ludlow Street Suite 400 Dayton, Ohio 45402
Phone: (937) 223-3621 Fax: (937) 223-3849

App Architecture
creative focused design
615 Woodside Drive, Englewood, Ohio 45322
T 937.836.8598 F 937.832.3696
www.app-arch.com



Beavercreek Township

Fire Station No. 65


1777 Trebein Road, Beavercreek Township, Ohio 45385

ISSUE:		
NO.	DATE	DESCRIPTION
04/03/20	3541.00	FOR CONSTRUCTION

DATE	04/03/20
JOB NO.	3541.00
DRAWN	DAC
CHECKED	TCR
CAD	16544E0.6

COPYRIGHT © 2020 App Architecture, Inc.
TITLE
TECHNOLOGY DETAILS

SHEET NO.
E0.7



- # CONSTRUCTION NOTES
1.

COORDINATE ELECTRIC SERVICE UTILITY WITH DP&L FOR ROUTING OF UNDERGROUND SERVICE ENTRANCE CONDUCTORS FROM EXISTING PADMOUNT TRANSFORMER LOCATION. PROVIDE C/T CABINET AND METER ON BUILDING EXTERIOR (OR SINGLE PHASE SERVICE ENTRANCE METERING ENCLOSURE RATED FOR SERVICE AMPACITY PER DP&L STANDARDS). DP&L CONSTRUCTION PACKET SUBMITTED (WORK ORDER #10127772), DAVID HELMIG, PH: 937-331-3547.
2.

PROVIDE TWO 1" CONDUITS FROM MAIN ELECTRIC ROOM TO PULLBOX AT SOUTHWEST CORNER OF TREBEIN AND FAIRGROUND ROAD FOR FUTURE FIRE SIGNAL/TRAFFIC SIGNAL WIRING INTERFACE.
3.

PROVIDE UNDERGROUND CONDUITS FROM I.T. ROOM TO SITE TERMINATION FOR PHONE/CTV SERVICE TO STATION. FINAL COORDINATE TERMINATION POINT WITH OWNER'S SERVICE PROVIDER(S).
4.

SANITARY LIFT PUMP/GRINDER CONTROL PANEL FURNISHED/INSTALLED BY EQUIPMENT SUPPLIER, CONTROL PANEL LOCATED IN APPARATUS BAY. E.C. SHALL PROVIDE POWER TO CONTROL PANEL AND UNDERGROUND CONDUIT FROM CONTROL PANEL TO EXTERIOR LIFT STATION. WIRING FROM LIFT STATION CONTROL PANEL TO PUMP BY EQUIPMENT SUPPLIER. COORDINATE LOCATIONS WITH EQUIPMENT SUPPLIER. FED FROM PANEL "SP3".
5.

COORDINATE CONDUIT SIZE REQUIRED BY SANITARY LIFT PUMP SUPPLIER (PRE-TERMINATED WIRING BY EQUIPMENT SUPPLIER).
6.

LIFE-SAFETY AND STANDBY POWER FEEDERS AS WELL AS START SIGNAL WIRING FROM GENERATOR TO A.T.S.'s BY E.C. PROVIDE REMOTE STOP WIRING FROM GENERATOR TO EM STOP BUTTON IN MAIN ELECTRIC ROOM (LOCATED NEXT TO A.T.S.'s. PROVIDE ANNUNCIATOR WIRING FROM GENERATOR TO REMOTE ANNUNCIATOR (IN CORRIDOR) COORDINATE WIRING REQUIREMENTS WITH GENERATOR SUPPLIER. PROVIDE MINIMUM OF 4 SPARE CONTROL WIRES TO EACH A.T.S.. PROVIDE WIRING FROM EACH A.T.S. TO REMOTE ANNUNCIATOR FOR A.T.S. POSITION INDICATION.
7.

PROVIDE DEDICATED 20A-120V CIRCUITS TO GENERATOR HOUSING FOR ENGINE BLOCK HEATER AND BATTERY CHARGER.
8.

CIRCUIT EXTERIOR LIGHTING THRU LIGHTING CONTROL RELAY PANEL (MEZZANINE).
9.

POLE LIGHT LOCATION ADJUSTED TO THE NORTH IF ALTERNATE FOR BYPASS DRIVE IS ACCEPTED.




ISSUE:		
NO.	DATE	DESCRIPTION
04/03/20	FOR CONSTRUCTION	

DATE	04/03/20
JOB NO.	3541.00
DRAWN	DAC
CHECKED	TCR
CAD	18102E1.1

COPYRIGHT © 2020 App Architecture, Inc.

TITLE
ELECTRICAL
SITE PLAN

SHEET NO.
E1.1



STORM SHELTER NOTES

A. PENETRATIONS THROUGH THE STORM SHELTER ENVELOPE LARGER THAN 3-1/2" IN AREA FOR RECTANGULAR OPENINGS OR 2-1/16" IN DIAMETER SHALL BE CONSIDERED OPENING AND SHALL BE PROVIDED WITH AN OPENING PROTECTIVE DEVICE. REFERENCE STRUCTURAL DRAWINGS.

B. LIGHTING FIXTURES IN STORM SHELTER SHALL HAVE INTEGRAL EMERGENCY BATTERY BALLAST(S) IN FIXTURE(S) CAPABLE TO ILLUMINATE FIXTURE AT 1000 LUMENS FOR A MINIMUM OF 180 MINUTES (2 HOURS) OR THE E.C. SHALL PROVIDE SEPARATE EMERGENCY BATTERY LIGHTING UNIT WITH SIMILAR LUMEN OUTPUT AND BATTERY BACKUP.

CONSTRUCTION NOTES


1. CONNECT SHOWER LIGHT TO GROUND-FAULT-FEED-THRU OF TOILET ROOM RECEPTACLE.

2. PROVIDE DEDICATED 20A-120V CIRCUIT FOR ALL "F3" RED CALL SIGNAL LIGHTS AND "S1" RED SIGNAL STROBES IN APPARATUS BAY AND ON EXTERIOR. PROVIDE ELECTRICALLY HELD LIGHTING CONTACTOR (CONNECTED TO CALL SYSTEM OUTPUT RELAY, LOCATED IN IT ROOM) AND CONNECT ALL SIGNALING LIGHTS TO CONTACTOR TO ILLUMINATE LIGHTS UPON SYSTEM ALARM CALL.

3. APPARATUS BAY CONTROL PANEL FLUSH MOUNTED IN WALL. REFER TO DETAIL ON SHEET E0.4. PANEL INCLUDES CONTROL FOR APPARATUS BAY LIGHTS, AIR CIRCULATION FANS, KITCHEN GAS/POWER SHUTOFF AND MANUAL OVERRIDES FOR APPARATUS BAY EXHAUST SYSTEM AND HEAT.

4. APPARATUS BAY LIGHTING WIRED CONTROLLED THRU LIGHTING CONTROL RELAY PANEL. REFER TO SCHEDULE ON SHEET E0.2.

5. EXTERIOR LIGHTING WIRED/CONTROLLED THRU LIGHTING CONTROL RELAY PANEL. REFER TO SCHEDULE ON SHEET E0.2.




BEAVERCREEK TOWNSHIP
FIRE STATION No. 65
1777 TREBEN ROAD
BEAVERCREEK TOWNSHIP, OHIO 45385

ISSUE:		
NO.	DATE	DESCRIPTION
1	04/03/2020	FOR CONSTRUCTION
	05/04/2020	CODE REVISIONS

DATE	04/03/2020
JOB NO.	3541.00
DRAWN	TSR
CHECKED	JDZ
CAD	-
COPYRIGHT © 2020 App Architecture, Inc.	

TITLE
LIGHTING PLANS

SHEET NO.
E2.1



CONSTRUCTION NOTES


1. PROVIDE NEMA 5-20R RECEPTACLE AT CEILING STRUCTURE FOR CONNECTION OF RETRACTABLE CORD REEL. LOCATE ADJACENT TO COMPRESSED AIR HOSE REEL.
2. RECEPTACLE LOCATED ABOVE COUNTERTOP/BACKSPLASH IN PARTIAL HEIGHT WALL. ORIENT DEVICE HORIZONTALLY. RECEPTACLE CIRCUIT WIRED THRU RELAY PANEL TO CONTROL KITCHEN EQUIPMENT CIRCUITS THRU "EM" STOP/RESET BUTTONS.
3. MOUNT KITCHEN RANGE RECEPTACLE NEAR BASE OF WALL. RECEPTACLE WIRED THRU RELAY PANEL TO CONTROL KITCHEN EQUIPMENT CIRCUITS THRU "EM" STOP/RESET BUTTONS. (SP1-2/4).
4. PROVIDE SWITCHED SINGLE RECEPTACLE IN SINK BASE CABINET FOR GARBAGE DISPOSER. LOCATE SWITCH ABOVE COUNTER ADJACENT TO SINK. PROVIDE MATCHING CORD AND PLUG ON DISPOSER. COORDINATE WITH P.C.
5. COORDINATE RECEPTACLE CONFIGURATION FOR COFFEE MAKER PRIOR TO SUBMITTAL/INSTALLATION.
6. KITCHEN COUNTER-TOP RECEPTACLES WIRED THRU RELAY PANEL TO DE-ENERGIZE UPON INITIATION OF "EM" STOP BUTTON LOCATED ADJACENT TO APPARATUS BAY DOOR. "EM" STOP BUTTON TO BE RED MUSHROOM HEAD TYPE BUTTON, MAINTAINED CONTACT TYPE (PULL TO RESET). "EM" BUTTON/RELAY PANEL TO DE-ENERGIZE (OPEN) GAS SOLENOID VALVE SERVING KITCHEN RANGE AND GAS GRILLE. COORDINATE VALVE LOCATION AND WIRING REQUIREMENTS WITH P.C.
7. LOCATE RECEPTACLE(S) IN PARTIAL HEIGHT WALL 12" BELOW PENINSULA COUNTERTOP.
8. PROVIDE 3/4" FIRE RETARDANT PLYWOOD ON 3 WALLS OF IT ROOM. CONTINUOUS FROM 6" TO 8'-6" A.F.F. ALL RECEPTACLES IN IT ROOM SURFACE MOUNTED ON PLYWOOD. PROVIDE DEDICATED 30 AMP-120V CIRCUIT TO EACH DATA RACK FROM OVERHEAD CORD DROP (NEMA L5-30R CORD CONNECTOR). TOTAL OF 3 DATA RACKS. COORDINATE LOCATIONS OF DATA RACK/TECHNOLOGY CABINETS WITH TECHNOLOGY CONTRACTOR(S).
9. PROVIDE FLUSH WALL MOUNTED FAN SPEED CONTROLLER (HI-MED-LOW SPEED AND OFF) AND WIRE TO CONTROL ROOM CEILING FAN. REFER TO SPECIFICATIONS.
10. PROVIDE FIRE ALARM CONTROL RELAY TO STOP (DISCONNECT POWER) TO APPARATUS BAY CEILING FAN UPON ALARM CONDITION.
11. PROVIDE FIRE ALARM RELAYS IN I.T. ROOM FOR INTERCONNECTION TO CLEAN AGENT FIRE SUPPRESSION SYSTEM TO PROVIDE ALARM(S) UPON SUPPRESSION SYSTEM ACTIVATION AND TO SHUT DOWN ROOM A/C UNIT PRIOR TO ACTIVATION. COORDINATE SYSTEM TROUBLE/PRE-ALARM/ALARM CONDITIONS FOR MONITORING/ALARM REQUIREMENTS AND INTERLOCK WIRING REQUIREMENTS TO ROOM A/C UNIT WITH H.C.
12. PROVIDE DEDICATED CIRCUIT TO RECEPTACLE IN SINK BASE CABINET FOR DISHWASHER. SP1- (GFCI BREAKER).
13. PROVIDE NEMA 14-50R RECEPTACLE AND DEDICATED CIRCUIT FOR GAS RANGE. SP1- (GFCI BREAKER). CIRCUIT THRU RELAY PANEL FOR CONTROL THRU KITCHEN EM STOP BUTTON.
14. COORDINATE RECEPTACLE MOUNTING HEIGHT FOR ABOVE COUNTER MICROWAVE OVEN.
15. PROVIDE HOSE HOIST. MOUNTED TO CEILING/WALL STRUCTURE NEAR CEILING PEAK. REFER TO STRUCTURAL DRAWINGS FOR SUPPORT STRUCTURE TO MOUNT HOIST. HOIST SHALL HAVE 500 POUND LIFTING CAPACITY. WITH STAINLESS STEEL CABLE. SINGLE ATTACHMENT HOOK AND MINIMUM 30 FOOT TRAVEL LENGTH. EQUAL TO ELECTROLIFT MODEL #207-LG. 240V-1PH MOTOR WITH 120V CONTROL. PROVIDE HARDWIRED REMOTE CONTROL STATION. FLUSH MOUNTED UP/DOWN/STOP BUTTON. PROVIDE FUSED DISCONNECT SWITCH ON WALL IN BAY FOR MOTOR SERVICE DISCONNECT.
16. APPARATUS BAY CONTROL PANEL. FLUSH MOUNTED IN WALL. REFER TO DETAIL. SHEET E0.4
17. COORDINATE POWER REQUIREMENTS TO AIR COMPRESSOR WITH P.C.
18. COORDINATE POWER TO GAS SOLENOID VALVE WITH P.C. WIRED THRU RELAY PANEL FOR CONTROL FROM "EM STOP" SWITCH APPARATUS BAY CONTROL PANEL REFER TO DETAIL. SHEET E0.4.
19. PROVIDE TV ROUGH-IN BOX ON WALL. 84" M.H. WITH ADDITIONAL RECEPTACLE/DATA ROUGH-IN ON WALL BELOW FOR LOCAL VIDEO INPUT DEVICE. PROVIDE 1.25" CONDUIT FROM TV ROUGH-IN BOX TO DATA BOX BELOW FOR INTERCONNECTION CABLING (BY OWNER).
20. PROVIDE TWO FLUSH MOUNTED SINGLE-GANG BOXES (46" M.H.) WITH 3/4" CONDUIT TO ACCESS CONTROL SYSTEM FOR ENTRY DOOR MAG-LOCK. COORDINATE INSTALLATION WITH HARDWARE SUPPLIER.
21. PROVIDE RECEPTACLE BELOW SINK IN BASE CABINET FOR DISHWASHER CONNECTION. REFER TO PANEL "SP1" SCHEDULE FOR CIRCUIT. PROVIDE CORD & PLUG CONNECTION ON DISHWASHER.
22. PROVIDE TWO TIERS OF PLUGMOLD ON WALL (LOCATED ABOVE SHELVES). 4" LONG PLUGSTRIP WITH NEMA 5-15R RECEPTACLES & O.C.
23. REFER TO PANEL SCHEDULE "LS1" FOR CIRCUITS IN I.T. ROOM.
24. REFER TO PANEL SCHEDULE "SP3" FOR FURNACE CIRCUITS.
25. PROVIDE 20A-120V CIRCUIT FROM PANEL "LS1" TO FM. 200
26. ACCESS CONTROL PANEL
27. FIRE ALARM ANNUNCIATOR

ISSUE:		
NO.	DATE	DESCRIPTION
1	05/04/2020	FOR CONSTRUCTION CODE REVISIONS

DATE	04/03/2020
JOB NO.	3541.00
DRAWN	TSR
CHECKED	JDZ
CAD	-

COPYRIGHT © 2020 App Architecture, Inc.
TITLE
POWER PLANS

SHEET NO.
E3.1



CONSTRUCTION NOTES

- COORDINATE CONDUIT PATHWAY FROM DOOR POSITION SWITCH ON OVERHEAD DOORS TO ACCESS CONTROL/SECURITY SYSTEM IN I.T. ROOM.
- PROVIDE CONTROL/MONITOR MODULE FOR INTERFACE WITH FM 200 SYSTEM PANEL. COORDINATE REQUIREMENTS WITH SYSTEM SUPPLIER.

App Architecture
creative focused design

615 Woodside Drive, Englewood, Ohio 45322
T 937.836.8898 F 937.832.3696
www.app-arch.com



BEAVERCREEK TOWNSHIP
FIRE STATION No. 65
1777 TREBEN ROAD
BEAVERCREEK TOWNSHIP, OHIO 45385

ISSUE:	
NO.	DATE DESCRIPTION

DATE	04/03/2020
JOB NO.	3541.00
DRAWN	TCR
CHECKED	JDZ
CAD	-

COPYRIGHT © 2020 App Architecture, Inc.

TITLE
SYSTEMS PLANS

SHEET NO.
E4.1